




PRODUCT-DETAILS

AF190-30-11-13

AF190-30-11-13 Contactor



General Information	
Extended Product Type:	AF190-30-11-13
Product ID:	1SFL487002R1311
EAN:	7320500480434
Catalog Description:	AF190-30-11-13 Contactor
Long Description:	The AF190-30-11-13 is a 3 pole - 1000 V IEC or 600 V UL contactor with pre-mounted auxiliary contacts and Main Circuit Bars, controlling motors up to 90 kW / 400 V AC (AC-3) or 125 hp / 480 V UL and switching power circuits up to 275 A (AC-1) or 250 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (100-250 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories. Includes Mounting kit, containing all necessary screws, washers and sockets for connecting the terminals, and screws for mounting the device.
Display Name:	AF190-30-11-13

Ordering	
Minimum Order Quantity:	1 piece

Customs Tariff Number: 85364900

Popular Downloads

EPLAN Data:	9AAC174541_EPLAN
Data Sheet, Technical Information:	1SBC100214C0202
Data Sheet, Technical Information (Part 2):	1SAC200017M0002
Instructions and Manuals:	1SFC100008M0201
CAD Dimensional Drawing:	2CDC001079B0201

Dimensions

Product Net Width:	105 mm
Product Net Depth / Length:	152 mm
Product Net Height:	196 mm
Product Net Weight:	2.4 kg
Dimension Diagram:	1SFB535001G1056.pdf

Technical

Number of Main Contacts NO:	3
Number of Main Contacts NC:	0
Number of Auxiliary Contacts NO:	1
Number of Auxiliary Contacts NC:	1
Number of Poles:	3P
Rated Operational Voltage:	Main Circuit 1000 V
Rated Frequency (f):	Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th}):	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 275 A
Rated Operational Current AC-1 (I_e):	(1000 V) 40 °C 250 A (1000 V) 60 °C 225 A (1000 V) 70 °C 185 A (690 V) 40 °C 275 A (690 V) 60 °C 250 A (690 V) 70 °C 200 A
Rated Operational Current AC-3 (I_e):	(415 V) 60 °C 190 A (440 V) 60 °C 190 A (500 V) 60 °C 156 A (690 V) 60 °C 85 A (1000 V) 60 °C 85 A (380 / 400 V) 60 °C 190 A (220 / 230 / 240 V) 60 °C 190 A

Rated Operational Current AC-3e (I_e):	(415 V) 60 °C 190 A (440 V) 60 °C 190 A (500 V) 60 °C 135 A (690 V) 60 °C 135 A (1000 V) 60 °C 85 A (380 / 400 V) 60 °C 190 A (220 / 230 / 240 V) 60 °C 190 A
Rated Operational Current DC-1 (I_e):	(110 V) 2 Poles in Series, 40 °C 250 A (220 V) 3 Poles in Series, 40 °C 250 A
Rated Operational Current DC-3 (I_e):	(110 V) 2 Poles in Series, 40 °C 250 A (220 V) 3 Poles in Series, 40 °C 250 A
Rated Operational Current DC-5 (I_e):	(110 V) 2 Poles in Series, 40 °C 250 A (220 V) 3 Poles in Series, 40 °C 250 A
Rated Operational Power AC-3 (P_e):	(415 V) 90 kW (440 V) 110 kW (500 V) 110 kW (690 V) 132 kW (1000 V) 110 kW (380 / 400 V) 90 kW (220 / 230 / 240 V) 55 kW
Rated Operational Power AC-3e (P_e):	(415 V) 90 kW (440 V) 110 kW (500 V) 110 kW (690 V) 132 kW (1000 V) 110 kW (380 / 400 V) 90 kW (220 / 230 / 240 V) 55 kW
Rated Breaking Capacity AC-3:	8 x I_e AC-3
Rated Breaking Capacity AC-3e:	8.5 x I_e AC-3e
Rated Making Capacity AC-3:	10 x I_e AC-3
Rated Making Capacity AC-3e:	12 x I_e AC-3e
Short-Circuit Protective Devices:	gG Type Fuses 355 A
Rated Short-time Withstand Current Low Voltage (I_{cw}):	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 1520 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 275 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 621 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1900 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 878 A
Maximum Breaking Capacity:	cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 3300 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 2200 A
Rated Insulation Voltage (U_i):	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 1000 V
Rated Impulse Withstand Voltage (U_{imp}):	Main Circuit 8 kV
Maximum Electrical Switching Frequency:	(AC-1) 300 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 300 cycles per hour
Mechanical Durability:	5 million
Maximum Mechanical Switching Frequency:	300 cycles per hour
Coil Operating Limits:	(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)
Rated Control Circuit Voltage (U_c):	50 Hz 100 ... 250 V 60 Hz 100 ... 250 V DC Operation 100 ... 250 V

Coil Consumption:	Holding at Max. Rated Control Circuit Voltage 50 Hz 26.8 V-A Holding at Max. Rated Control Circuit Voltage 60 Hz 26.8 V-A Holding at Max. Rated Control Circuit Voltage DC 3.5 V-A Holding at Max. Rated Control Circuit Voltage DC 3.5 W Pull-in at Max. Rated Control Circuit Voltage 50 Hz 285 V-A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 285 V-A Pull-in at Max. Rated Control Circuit Voltage DC 360 V-A Pull-in at Max. Rated Control Circuit Voltage DC 360 W
Power Loss:	at Rated Operating Conditions per Pole 7 W
Operate Time:	Between Coil De-energization and NO Contact Opening 37 ... 47 ms Between Coil Energization and NO Contact Closing 25 ... 55 ms
Connecting Capacity Main Circuit:	Flexible 2 x 50 ... 95 mm ² Rigid Al-Cable 1 x 95 ... 185 mm ² Rigid Cu-Cable 1 x 6 ... 150 mm ²
Connecting Capacity Auxiliary Circuit:	Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible 2x0.75 ... 2.5 mm ² Solid 2 x 1 ... 4 mm ² Stranded 2 x 1 ... 4 mm ²
Connecting Capacity:	Flexible 1 x 6 ... 120 mm ² Rigid Al-Cable 1 x 95 ... 185 mm ² Rigid Cu-Cable 1 x 6 ... 150 mm ²
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Tightening Torque:	Cable Lug 18 N-m Main Circuit 14 ... 31 N-m
Terminal Type:	Main Circuit: Bars
Product Name:	Block Contactor

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 1000 V
General Use Rating UL/CSA:	(1000 V AC) 250 A (600 V AC) 275 A
Horsepower Rating UL/CSA:	(200 V AC) Three Phase 50 hp (208 V AC) Three Phase 50 hp (220 ... 240 V AC) Three Phase 60 hp (440 ... 480 V AC) Three Phase 125 hp (550 ... 600 V AC) Three Phase 150 hp
Full Load Amps Motor Use:	(440 ... 480 V AC) Three Phase 156 A (550 ... 600 V AC) Three Phase 144 A

Environmental

Ambient Air Temperature:	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C Close to Contactor for Storage -40 ... 70 °C
Maximum Operating Altitude Permissible:	Without Derating 3000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
---	-----------------

REACH Declaration:	2CMT2021-006202
RoHS Declaration:	2CMT2021-006277
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA:	2CMT2023-006525
WEEE B2C / B2B:	Business To Business
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)

ABB EcoSolutions

ABB EcoSolutions:	Yes
ABB Site Meeting Group Waste To Landfill Target:	Non-hazardous waste is sent to a landfill, where there is no alternative option available within 100km of a facility UL 2799 Zero Waste To Landfill Validation available
EcoSolutions Profile:	1SFC100125C0366
End Of Life Disassembling Instructions:	1SFC100112M0001
Environmental Product Declaration - EPD:	1SFC100095D0201 2TFP200018A1001
Extended Product Lifetime:	Product Durability
Improved Energy Efficiency for Customers:	Product Efficiency - Product requires less energy to operate compared to similar product on market or older products from the same line Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
Recyclability Rate of the Product acc. to EN45555:	Design for Closing Resource Loops - Standard EN45555 - 79.1 %

Certificates and Declarations

A2L Certificate – UL:	9AKK108468A6695
ABS Certificate:	14-LD1092198-PDA 14-LD1092198-1-PDA-DUP
BV Certificate:	BV_36353_A0BV
CB Certificate:	SE-82315
CCS Certificate:	GB14T00030 GZ15T00069
CQC Certificate:	CQC2014010304676685 CQC2014010304724672
cULus Certificate:	20121023-E36588
Declaration of Conformity - CE:	2CMT2015-005439
Declaration of Conformity - UKCA:	2CMT2020-006118
DNV Certificate:	DNV_E-14043
LR Certificate:	16-20064
PRS Certificate:	TE_2092_880423_16
RINA Certificate:	ELE060313XG_002
UL Listing Card:	UL_E36588

Container Information

Package Level 1 Units:	box 1 piece
Package Level 1 Width:	160 mm
Package Level 1 Depth / Length:	258 mm
Package Level 1 Height:	235 mm
Package Level 1 Gross Weight:	3 kg
Package Level 1 EAN:	7320500480434

External Classifications and Standards

Object Classification Code:	Q
ETIM 7:	EC000066 - Power contactor, AC switching
ETIM 8:	EC000066 - Power contactor, AC switching
ETIM 9:	EC000066 - Power contactor, AC switching
eClass:	V11.0 : 27371003
UNSPSC:	39121529
IDEA Granular Category Code (IGCC):	4758 >> lec Contactors
E-Number (Finland):	3706394
E-Number (Norway):	4117637
E-Number (Sweden):	3210134

Accessories

Identifier	Description	Type	Qty	Unit Of Measure
1SFN170801R1001	RU19/120 LVRT-Module	RU19/120	1	piece
1SFN170801R1002	RU19/240 LVRT-Module	RU19/240	1	piece

Categories

Products > Low Voltage Products and Systems > Control Products > Contactors > Block Contactors > AF Contactors > AF190
Parts & Services > Drives > Services > Spares and Consumables > Parts




ABB
Eco
Solutions™