

48290101

Control power supply system interface DIRIS Digiware C-31 RS485 output



Strong points

- Compact
- Safety Extra Low Voltage power supply 24 VDC

Compliance with standards

- IEC 61557-12
- UL 61010 Guide FTRZ/PICQ File E257746

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/48290101>

For applications without a local display DIRIS Digiware C-31 interfaces centralise all measurements and communicate data over RS485 to external software or a PLC.

The DIRIS Digiware C-31 interface is powered by 24 VDC.

Technical Characteristics

Model	C-31
Size	1 Module
Type	DIRIS Digiware RS485 system interface

Classification

UNSPSC	83101808
ETIM Class	EC002295
IGCC	6042

Commerce

Description	Control power supply interface Module DIRIS C-31 with RS485 Modbus RTU system interface for applications without a local display, supplied with 24 VDC, DIN-rail or backplate mounting
Effective date	2014-01-22
Offer Life Cycle Code	40
Country of origin	FR

ETIM - Technical features

Type of accessory/spare part	Other
------------------------------	-------

Logistics

GTIN/EAN	3596032783815
Customs number	8517620000
Price unit	PC
Weight of the packing unit [kg]	0.09
Length of the packing unit [m]	0.08
Width of the packing unit [m]	0.033
Depth of the packing unit [m]	0.12

Norms

Conformity to standards	IEC UL
-------------------------	-----------