

48290103

Control power supply bus repeater DIRIS Digiware C-32



Strong points

- Compact
- Safe
- Plug & Play

General characteristics

- 24 VDC powered.
- Max 2 repeaters can be used.

Compliance with standards

- IEC 61557-12
- UL 61010 Guide FTRZ/PICQ File E257746
- ANSI C12.20

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/48290103>

The DIRIS Digiware C-32 module is a bus repeater with a 24 VDC input that is used whenever the total power consumption exceeds the maximum consumption of the 24 VDC auxiliary power supply used. The C-32 repeater provides an additional 20 W and 100 metres to the Digiware bus.

A maximum of 2 repeaters can be used in the same system, allowing the Digiware bus to reach up to 300 metres.

Technical Characteristics

Model	C-32
Size	1 Module
Type	DIRIS Digiware Repeater

Classification

UNSPSC	83101808
ETIM Class	EC002295
IGCC	6042

Commerce

Description	Digiware bus repeater DIRIS C-32 24 VDC auxiliary power supply provide an additional 20 W and 100 metres to the Digiware bus, maximum of 2 repeaters can be used in the same system
Effective date	2014-01-22
Offer Life Cycle Code	40
Country of origin	FR

ETIM - Technical features

Type of accessory/spare part	Other
------------------------------	-------

Logistics

GTIN/EAN	3596032783822
Customs number	8543709099
Price unit	PC
Weight of the packing unit [kg]	0.09
Length of the packing unit [m]	0.03
Width of the packing unit [m]	0.08
Depth of the packing unit [m]	0.117

Norms

Conformity to standards	IEC UL
-------------------------	-----------