


48290594

RJ12 connection cable 2m x6



General characteristics

- Plug & Play.
- Colour coded.
- Multiple lengths.

Compliance with standards

- IEC 61557-12
- UL 61010 Guide FTRZ/PICQ File E257746

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/48290594>

The RJ12 connections allow you to connect modules very quickly and to automatically configure connected current sensors:

- communication address,
 - load type,
 - sensor type and ratio,
 - automatic rating and verification of current travel direction.
- Wiring errors are also prevented and installation is simplified.

Technical Characteristics

Height [mm]	2000
Color	Red, Black, Yellow, Blue, Green, Purple
Connector	RJ12
Length	2 m
Type	Connection cable for TE, TR/iTR, TF current sensors

Classification

UNSPSC	83101808
ETIM Class	EC001262
IGCC	6042

Commerce

Effective date	2014-01-10
Offer Life Cycle Code	40
Country of origin	TH

ETIM - Mechanical characteristics

Length [m]	2
Colour outer sheath	Grey
Anti-kink sleeve	None
Cable construction	Other
AWG-size	26
Cable type	U/UTP

ETIM - Technical features

Category	5
Type of connector connection 1	RJ12 6(6)
Type of connector connection 2	RJ12 6(6)
Locking lever	No
Fire retardant version	No
Oil resistant according to EN IEC 60811-404	Yes
Pin assignment	1:1
NVP value [%]	70

Logistics

GTIN/EAN	3596032781972
Customs number	8544429090
Price unit	PC
Weight of the packing unit [kg]	0.28
Length of the packing unit [m]	0.095
Width of the packing unit [m]	0.045
Depth of the packing unit [m]	0.125

Norms

Conformity to standards	IEC UL
-------------------------	-----------