



SIMATIC, terminal module TM-PS-A standard for ET200iSP, for holding the power supply module 120/230 V AC and 24 V DC, Ex eb [ia Ga/ib] IIC T4 Gb, Ex eb [ia IIIC Da] IIC T4 Gb, Ex eb [ia/ib] I Mb

General information	
Product type designation	TM-PS-A UC
Installation type/mounting	
Rack mounting	No
Front mounting	Yes
Rail mounting	Yes
Wall mounting/direct mounting	No
Supply voltage	
Type of supply voltage	AC
permissible range, lower limit (AC)	85 V
permissible range, upper limit (AC)	264 V
Input current	
At 50 Hz AC, max.	6 A
At 60 Hz AC, max.	6 A
Output voltage	
Type of output voltage	DC
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Output current	
At DC, max.	5 A
Hardware configuration	
Slots	
• Number of slots	1
• Plug-in modules, analog I/O	No
• Plug-in modules, digital I/O	No
• Plug-in modules, function modules and technology modules	No
• Plug-in modules, communication modules	No
• Plug-in modules, CPUs	No
• Plug-in modules, others	Yes
Isolation	
Isolation tested with	2500 V AC between control supply voltages and all output voltages
Standards, approvals, certificates	
CE mark	CE 0344
UKCA mark	DEKRA 21UKEX0032 Importer UK: Siemens plc Manchester M20 2UR
cULus	LISTED E334384
FM approval	CLASSIFIED 3025852
Suitable for safety functions	Yes
INMETRO certificate	UL-BR 12.0077

Use in hazardous areas	
• ATEX certificate	KEMA 04 ATEX 2242
• IECEx	IECEx KEM 05.0003
• CCC Ex	2020322310002881
• Explosion protection category for gas	ATEX gas explosion protection, Zone 1
• Explosion protection category for dust	ATEX dust explosion protection, Zone 21 always install in corresponding enclosure
• associated equipment (Ex ia)	No
• associated equipment (Ex ib)	No

Marine approval	
• Germanischer Lloyd (GL)	Yes
• American Bureau of Shipping (ABS)	Yes
• Bureau Veritas (BV)	Yes
• Det Norske Veritas (DNV)	Yes

Connection method

Terminals	
• Conductor cross-section, min.	0.5 mm ² ; note "Wiring rules for ET 200iSP"
• Conductor cross-section, max.	4 mm ²

Dimensions

Width	60 mm
Height	190 mm
Depth	52 mm

Weights

Weight, approx.	230 g
-----------------	-------

Classifications

	Version	Classification
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval



[Miscellaneous](#)

[China RoHS](#)



For use in hazardous locations



[FM](#)



[Miscellaneous](#)



For use in hazardous locations

[CCC-Ex](#)



[Miscellaneous](#)



Maritime application

Environment



last modified:

3/13/2026 