



Figure similar

SIMATIC S7-400, analog input SM 431, isolated 8 AI, resolution 13 bit, U/IResistor

Supply voltage	
Load voltage L+	
• Rated value (DC)	not necessary
Input current	
from backplane bus 5 V DC, max.	350 mA
Power loss	
Power loss, typ.	1.8 W
Analog inputs	
Number of analog inputs	8
• For voltage/current measurement	8
• For resistance measurement	4
permissible input voltage for voltage input (destruction limit), max.	50 V
permissible input current for current input (destruction limit), max.	50 mA; 40 mA continuous
Constant measurement current for resistance-type transmitter, typ.	1.67 mA
Input ranges	
• Voltage	Yes
• Current	Yes
• Thermocouple	No
• Resistance thermometer	No
• Resistance	Yes
Input ranges (rated values), voltages	
• 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	200 kΩ
• -1 V to +1 V	Yes
— Input resistance (-1 V to +1 V)	200 kΩ
• -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	200 kΩ
Input ranges (rated values), currents	
• -20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	80 Ω
• 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	80 Ω
Input ranges (rated values), resistors	
• 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	usable up to 500 ohms
Cable length	

• shielded, max.	200 m		
Analog value generation for the inputs			
Integration and conversion time/resolution per channel			
• Resolution with overrange (bit including sign), max.	13 bit		
• Integration time, parameterizable	Yes		
• Basic conversion time (ms)	23 / 25 ms		
• Integration time (ms)	16,7 / 20 ms		
• Interference voltage suppression for interference frequency f1 in Hz	50 / 60 Hz		
• Basic execution time of the module (all channels released)	200 ms; 184 / 200 ms		
Encoder			
Connection of signal encoders			
• for voltage measurement	Yes; possible		
• for current measurement as 2-wire transducer	Yes; with external transmitter supply		
• for current measurement as 4-wire transducer	Yes		
• for resistance measurement with two-wire connection	Yes; Line resistances are also measured		
• for resistance measurement with three-wire connection	Yes; Line resistances are also measured		
• for resistance measurement with four-wire connection	Yes		
Errors/accuracies			
Temperature error (relative to input range), (+/-)	0.02 %/K; ±0.02 %/K in impedance measuring range; ±0.007 % in all other measuring ranges		
Operational error limit in overall temperature range			
• Voltage, relative to input range, (+/-)	1 %; ±1.0 % at ±1 V; ±0.6 % at ±10 V; ±0.7 % at 1 to 5 V		
• Current, relative to input range, (+/-)	1 %; at ±20 mA, 4 to 20 mA		
• Resistance, relative to input range, (+/-)	1.25 %; 0 to 500 ohms (4-conductor measurement, in range of 600 ohms)		
Basic error limit (operational limit at 25 °C)			
• Voltage, relative to input range, (+/-)	0.7 %; 0.7% at ±1 V; 0.4% at ±10 V; 0.5% at 1 to 5 V		
• Current, relative to input range, (+/-)	0.7 %; at ±20 mA, 4 to 20 mA		
• Resistance, relative to input range, (+/-)	0.8 %; 0 to 500 ohms (4-conductor measurement, in range of 600 ohms)		
Interrupts/diagnostics/status information			
Diagnostics function	No		
Potential separation			
Potential separation analog inputs			
• Potential separation analog inputs	Yes; internal/external		
• between the channels	No		
• between the channels and backplane bus	Yes		
Isolation			
Isolation tested with	2 120 V DC between bus and analog part; 500 V DC between bus and local ground; 2 120 V DC between analog part and local ground		
Dimensions			
Width	25 mm		
Height	290 mm		
Depth	210 mm		
Weights			
Weight, approx.	500 g		
Classifications			
		Version	Classification
	eClass	14	27-24-22-01
	eClass	12	27-24-22-01
	eClass	9.1	27-24-22-01
	eClass	9	27-24-22-01
	eClass	8	27-24-22-01
	eClass	7.1	27-24-22-01
	eClass	6	27-24-22-01
	ETIM	10	EC001420
	ETIM	9	EC001420
	ETIM	8	EC001420

ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[China RoHS](#)



[Metrological Approval](#)

General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------



[EM](#)

For use in hazardous locations	Maritime application
--------------------------------	----------------------



[Type Examination Certificate](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



Maritime application

[CCS \(China Classification Society\)](#)

last modified: 6/7/2025