



SIMATIC S7-400, analog output SM 432, isolated 8 AO; resolution 13 bit, U/I

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from supply and load voltage L+ (without load), max.	200 mA; at rated load: max. 400 mA
from backplane bus 5 V DC, max.	150 mA
Power loss	
Power loss, typ.	9 W
Analog outputs	
Number of analog outputs	8
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	30 mA
Current output, no-load voltage, max.	19 V
Output ranges, voltage	
• 0 to 10 V	Yes
• 1 V to 5 V	Yes
• -10 V to +10 V	Yes
Output ranges, current	
• 0 to 20 mA	Yes
• -20 mA to +20 mA	Yes
• 4 mA to 20 mA	Yes
Connection of actuators	
• for voltage output two-wire connection	Yes; possible, without compensation of the line resistances
• for voltage output four-wire connection	Yes; possible
• for current output two-wire connection	Yes; possible
Load impedance (in rated range of output)	
• with voltage outputs, min.	1 kΩ
• with voltage outputs, capacitive load, max.	1 μF
• with current outputs, max.	500 Ω; 600 ohms if common-mode-voltage reduced to <1 V
Cable length	
• shielded, max.	200 m
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	13 bit
• Conversion time (per channel)	420 μs; 420 μs in the ranges 1 to 5 V and 4 to 20 mA; 300 μs in all ranges
Settling time	
• for resistive load	0.1 ms
• for capacitive load	3.5 ms

• for inductive load		0.5 ms			
Errors/accuracies					
Operational error limit in overall temperature range					
• Voltage, relative to output range, (+/-)	0.5 %; ±10 V, 0 to 10 V, 1 to 5 V				
• Current, relative to output range, (+/-)	1 %; ±20 mA, 4 to 20 mV				
Basic error limit (operational limit at 25 °C)					
• Voltage, relative to output range, (+/-)	0.5 %; ±10 V, 0 to 10 V, 1 to 5 V				
• Current, relative to output range, (+/-)	0.5 %; ±20 mA, 0 to 20 mA				
Interrupts/diagnostics/status information					
Diagnostics function	No				
Potential separation					
Potential separation analog outputs					
• between the channels	No				
• between the channels and backplane bus	Yes				
• Between the channels and load voltage L+	Yes				
Isolation					
Isolation tested with	2 120 V DC between bus and L+/M; 2 120 V DC between bus and analog section; 500 V DC between bus and local ground; 500 V DC between analog section and L+/M; 2 120 V DC between analog section and local ground; 2 120 V DC between L+/M and local ground				
Dimensions					
Width	25 mm				
Height	290 mm				
Depth	210 mm				
Weights					
Weight, approx.	650 g				
Classifications					
		Version	Classification		
	eClass	14	27-24-22-01		
	eClass	12	27-24-22-01		
	eClass	9.1	27-24-22-01		
	eClass	9	27-24-22-01		
	eClass	8	27-24-22-01		
	eClass	7.1	27-24-22-01		
	eClass	6	27-24-22-01		
	ETIM	10	EC001420		
	ETIM	9	EC001420		
	ETIM	8	EC001420		
	ETIM	7	EC001420		
	IDEA	4	3562		
	UNSPSC	15	32-15-17-05		
Approvals / Certificates					
General Product Approval					
	China RoHS	Miscellaneous			Metrological Approval
General Product Approval		EMV	For use in hazardous locations		
					
For use in hazardous locations				Maritime application	

FM



Type Examination Cer-
tificate



Maritime application



NK / Nippon Kaiji Ky-
okai



Maritime application



CCS (China Classification Society)

last modified:

6/7/2025