



Figure similar

SIMATIC DP, Bus connection plug for PROFIBUS with slanted cable outlet, max 1.5 Mbaud, (W x H x D): 16 x 72.7 x 34 mm insulation displacement terminations, with connectible, passive bus termination for RS485-IS circuit, without PG connection socket, can only be used on Ex I PROFIBUS devices

Classifications

	Version	Classification
eClass	14	27-24-26-92
eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval

[China RoHS](#)

[Manufacturer Declaration](#)


EG-Konf.



[Miscellaneous](#)



General Product Approval EMV For use in hazardous locations


RCM


RCM


ATEX


IECEX


IECEX

[Miscellaneous](#)

For use in hazardous locations Maritime application



[Miscellaneous](#)



Maritime application



[NK / Nippon Kaiji Ky-
okai](#)



last modified:

6/7/2025