


95734016

Automatic Transfer Switch ATyS p 4P 160A



Strong points

- Recording of events
- Optional communication modules
- Configuration software
- Power measurements
- Possibility to set periodic genset startup
- Webserver
- Security and reliability

General characteristics

- Range from 125A to 3200A.
- Available in 3P or 4P.
- Recording of events.
- Robust design
- Safety and reliability.

Compliance with standards

- IEC 60947-6-1
- IEC 60947-3
- GB/T 14048.11

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/95734016>

ATyS p are 3 or 4 pole automatic transfer switches with positive break indication. They incorporate all the functions offered by the ATyS t and g, as well as functions designed for power management and functions communication.

In automatic mode they enable the monitoring of, and the on-load changeover between, two power supply sources, in accordance with the parameters configured through LCD display, or via communication. They are intended for use in low voltage power supply systems where a brief interruption of the load supply is acceptable during transfer.

Technical Characteristics

Height [mm]	135
Width [mm]	317
Depth [mm]	244
Weight [kg]	11.3
Control operator	Automatic fully programmable
Number of poles	4
Rated current [A]	160
Type	Class PC
Frame size	B3

Classification

UNSPSC	39122205
ETIM Class	EC000216
IGCC	5177

Commerce

Description	Automatic Transfer Switch ATyS p, switching type I-O-II, 4P 160A, the device can communicate in Modbus / Ethernet and Easyconfig software is available, replaceable motor and back plate mounting for Mains-Mains & Mains-Genset applications
Effective date	2012-06-21
Offer Life Cycle Code	40
Country of origin	FR

Environmental Sustainability

Climate change - Total - Cradle to Grave [kg CO ₂ eq.]	1939
Climate change - Total - Cradle to Gate [kg CO ₂ eq.]	121
SVHC > 0.1 mass percentage?	No
RoHS applicable?	Yes

ETIM - Electrical characteristics

Max. rated operation voltage Ue AC [V]	800
Rated operating voltage [V]	380..690
Rated permanent current Iu [A]	160
Rated permanent current at AC-23, 400 V [A]	160
Rated permanent current at AC-21, 400 V [A]	160
Rated short-time withstand current Icw [kA]	7
Rated operation power at AC-23, 400 V	80

[kW]	
Switching power at 400 V [kW]	1280
Conditioned rated short-circuit current I _q [kA]	100
Number of poles	4
ETIM - Mechanical characteristics	
Suitable for floor mounting	No
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	No
Suitable for intermediate mounting	Yes
Colour control element	Other
Degree of protection (IP), front side	IP20
Width [mm]	317
Height [mm]	135
Depth [mm]	244
ETIM - Technical features	
Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	No
Version as reversing switch	Yes
Number of switches	2
Number of auxiliary contacts as normally open contact	3
Motor drive optional	No
Motor drive integrated	Yes
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Type of control element	Other
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection
Logistics	
GTIN/EAN	3596032776091
Customs number	8536508000
Price unit	PC
Weight of the packing unit [kg]	11.3
Length of the packing unit [m]	0.36
Width of the packing unit [m]	0.375
Depth of the packing unit [m]	0.472
Norms	
Conformity to standards	CCC IEC