

Product datasheet

Specifications



screw shield - 4 poles - 72 mm - for iC60, iID, Reflex iC60, iSW-NA

Local distributor code:

396734967

A9A26981

EAN Code: 3606480088100

Main

Product or component type	Screw shield
Accessory / separate part category	Insulation accessory
Quantity per set	Set of 20
Colour	White

Complementary

Range compatibility	Acti9 iSW-NA Acti9 iC60 Acti9 iID Acti9 Reflex iC60
Poles description	3P 4P 1P + N 2P 3P + N 1P
mounting mode	By clips
[Ui] rated insulation voltage	500 V
Connection pitch	72 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.600 cm
Package 1 Width	7.400 cm
Package 1 Length	10.100 cm
Package 1 Weight	99.500 g
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.318 kg

Logistical informations

Country of origin	HU
-------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	3eb221ac-bf4a-4cb7-a765-7d1ef77c84ba
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Halogen free plastic parts product
PVC free	Yes

Use Again

Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No

Image of product in real life situation

