

# Product datasheet

Specifications



## Acti9 iC60N 2P 25A D Miniature Circuit Breaker

A9F45225

EAN Code: 3606480513855

### Main

|                           |                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                     | Acti9                                                                                                                                                                                                                                                                                                                                                                                             |
| Product name              | Disbo iC60                                                                                                                                                                                                                                                                                                                                                                                        |
| Product or component type | Miniature circuit-breaker                                                                                                                                                                                                                                                                                                                                                                         |
| Device short name         | IC60N                                                                                                                                                                                                                                                                                                                                                                                             |
| Poles description         | 2P                                                                                                                                                                                                                                                                                                                                                                                                |
| Number of protected poles | 2                                                                                                                                                                                                                                                                                                                                                                                                 |
| [In] rated current        | 25 A                                                                                                                                                                                                                                                                                                                                                                                              |
| Network type              | AC/DC                                                                                                                                                                                                                                                                                                                                                                                             |
| Trip unit technology      | Thermal-magnetic                                                                                                                                                                                                                                                                                                                                                                                  |
| Curve code                | D                                                                                                                                                                                                                                                                                                                                                                                                 |
| Breaking capacity         | 36 kA Icu at 12...133 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>20 kA Icu at 220...240 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>10 kA Icu at 380...415 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>6 kA Icu at 440 V AC 50/60 Hz conforming to EN/IEC 60947-2<br>10 kA Icu at <= 125 V DC conforming to EN/IEC 60947-2<br>6000 A Icn at 400 V AC 50/60 Hz conforming to EN/IEC 60898-1 |
| Utilisation category      | Category A conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                                           |

### Complementary

|                                        |                                                                                                                                                                                                                                                                                                                                       |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network frequency                      | 50/60 Hz                                                                                                                                                                                                                                                                                                                              |
| [Ue] rated operational voltage         | 12...133 V AC 50/60 Hz<br>220...240 V AC 50/60 Hz<br>380...415 V AC 50/60 Hz<br>440 V AC 50/60 Hz<br><= 125 V DC                                                                                                                                                                                                                      |
| Magnetic tripping limit                | 12 x In +/- 20 %                                                                                                                                                                                                                                                                                                                      |
| [Ics] rated service breaking capacity  | 27 kA 75 % conforming to EN/IEC 60947-2 - 12...133 V AC 50/60 Hz<br>15 kA 75 % conforming to EN/IEC 60947-2 - 220...240 V AC 50/60 Hz<br>7.5 kA 75 % conforming to EN/IEC 60947-2 - 380...415 V AC 50/60 Hz<br>4.5 kA 75 % conforming to EN/IEC 60947-2 - 440 V AC 50/60 Hz<br>10 kA 100 % conforming to EN/IEC 60947-2 - <= 125 V DC |
| Limitation class                       | 3 conforming to EN/IEC 60898-1                                                                                                                                                                                                                                                                                                        |
| [Ui] rated insulation voltage          | 500 V AC 50/60 Hz conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                        |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                                     |
| Contact position indicator             | Yes                                                                                                                                                                                                                                                                                                                                   |
| Control type                           | Toggle                                                                                                                                                                                                                                                                                                                                |
| Local signalling                       | Trip indicator                                                                                                                                                                                                                                                                                                                        |
| Mounting mode                          | Clip-on                                                                                                                                                                                                                                                                                                                               |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                          |                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------|
| Mounting support         | Rail                                                                                                    |
| 9 mm pitches             | 4                                                                                                       |
| Height                   | 85 mm                                                                                                   |
| Width                    | 36 mm                                                                                                   |
| Depth                    | 78.5 mm                                                                                                 |
| Product weight           | 0.25 kg                                                                                                 |
| Colour                   | White                                                                                                   |
| Mechanical durability    | 20000 cycles                                                                                            |
| Electrical durability    | 10000 cycles                                                                                            |
| Provision for padlocking | Padlockable                                                                                             |
| Connections - terminals  | Single terminal (top or bottom) 1...25 mm² rigid<br>Single terminal (top or bottom) 1...16 mm² flexible |
| Wire stripping length    | 14 mm for top or bottom connection                                                                      |
| Tightening torque        | 2 N.m top or bottom                                                                                     |
| Earth-leakage protection | Separate block                                                                                          |

## Environment

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Standards                             | EN/IEC 60947-2<br>EN/IEC 60898-1 |
| IP degree of protection               | IP20 conforming to IEC 60529     |
| Pollution degree                      | 3 conforming to EN/IEC 60947-2   |
| Overvoltage category                  | IV                               |
| Tropicalisation                       | 2 conforming to IEC 60068-1      |
| Relative humidity                     | 95 % at 55 °C                    |
| Ambient air temperature for operation | -35...70 °C                      |
| Ambient air temperature for storage   | -40...85 °C                      |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 7.0 cm   |
| Package 1 Width              | 3.5 cm   |
| Package 1 Length             | 9.0 cm   |
| Package 1 Weight             | 229.0 g  |
| Unit Type of Package 2       | BB1      |
| Number of Units in Package 2 | 6        |
| Package 2 Height             | 8.5 cm   |
| Package 2 Width              | 9.5 cm   |
| Package 2 Length             | 22.0 cm  |
| Package 2 Weight             | 1.435 kg |
| Unit Type of Package 3       | S03      |
| Number of Units in Package 3 | 66       |

|                  |           |
|------------------|-----------|
| Package 3 Height | 30.0 cm   |
| Package 3 Width  | 30.0 cm   |
| Package 3 Length | 40.0 cm   |
| Package 3 Weight | 16.272 kg |

## Logistical informations

|                   |    |
|-------------------|----|
| Country of origin | BG |
|-------------------|----|

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

|  Environmental footprint |                                               |
|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------|
| Total lifecycle Carbon footprint                                                                          | 35 kg CO2 eq.                                 |
| Carbon footprint of the manufacturing phase [A1 to A3]                                                    | 2 kg CO2 eq.                                  |
| Carbon footprint of the distribution phase [A4]                                                           | 0 kg CO2 eq.                                  |
| Carbon footprint of the installation phase [A5]                                                           | 0 kg CO2 eq.                                  |
| Carbon footprint of the use phase [B2, B3, B4, B6]                                                        | 32 kg CO2 eq.                                 |
| Carbon footprint of the end-of-life phase [C1 to C4]                                                      | 0.6 kg CO2 eq.                                |
| Environmental Disclosure                                                                                  | <a href="#">Product Environmental Profile</a> |

Use Better

|  Materials and Substances |                                                                                        |
|-------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| Packaging made with recycled cardboard                                                                      | Yes                                                                                    |
| Packaging without single use plastic                                                                        | Yes                                                                                    |
| SCIP Number                                                                                                 | 26ff71d1-98cf-4280-8725-455b9a6b2fb9                                                   |
| EU RoHS Directive                                                                                           | <a href="#">Compliant</a>                                                              |
| REACH Regulation                                                                                            | <a href="#">Reference contains Substances of Very High Concern above the threshold</a> |
| Halogen-free status                                                                                         | Halogen free plastic parts product                                                     |
| PVC free                                                                                                    | Yes                                                                                    |
| Silicone-free                                                                                               | No                                                                                     |

Use Longer

|  Lifetime extension |    |
|--------------------------------------------------------------------------------------------------------|----|
| Repair                                                                                                 | No |

Use Again

|  Repack and remanufacture |                                                                                                                                                                                                                 |
|--------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recyclability potential, in %                                                                                | 54                                                                                                                                                                                                              |
| End of life manual availability                                                                              | No need of specific recycling operations                                                                                                                                                                        |
| Take-back                                                                                                    | No                                                                                                                                                                                                              |
| WEEE Label                                                                                                   |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |



Offer Marketing Illustration

Product benefits / Features

Technical Benefits  
Acti9 iC60

