

Product datasheet

Specifications



APC Easy UPS, 900VA, Tower, 230V, 4x IEC C13 outlets, AVR

BVX900LI

EAN Code: 0731304404491

Main

Main input voltage	230 V AC 1 phase
Input connection	IEC 60320 C14
Cos phi	0.53
Efficiency at full load	140...300 V 230 V AC
Input frequency	50/60 Hz +/- 5 Hz auto-sensing
Output voltage	230 V AC 1 phase
Rated power in W	480 W
Rated power in VA	900 VA
Output connection	4 IEC 320 C13
Type of USB power supply	None
Maximum configurable power in VA	900 VA
Maximum configurable power in W	480 W
Transfer time	6 ms typical : 10 ms maximum
UPS topology	Line interactive
Waveform type	Stepped approximation to a sinewave
Full load runtime	00:01:00 480 W
Half load runtime	00:06:30 240 W
Output frequency	50/60 Hz +/- 1 Hz sync to mains

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Battery capacity	9.0 Ah
Battery type	Lead-acid internal included
Control panel	LED Status display with on line : on battery
Surge energy rating	273 J
Cable length	1.2 m
Number of cables	1
Color	Black

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	160 mm
Width	120 mm
Depth	355 mm
Product weight	6 kg
Mounting support	Floor
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Mounting mode	Desktop installation compact
Provided equipment	User manual
Max runtime	120 min
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of product	Easy UPS
Product or component type	Uninterruptible power supply (UPS)

Environment

Product certification	CE CB
Standard	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...40 °C
Storage altitude	0...3000 m
IP protection	IP20
Relative humidity	0...95 % non-condensing
Storage relative humidity	0...95 % non-condensing
Acoustic level	40 dBA
Operating altitude	0...3000 m

Batteries & Runtime

Battery type	Lead-acid battery
Battery voltage	12 V
Battery graph comment	Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0) output.
Extendable runtime	0
Included battery module	0
Empty battery slot	0
Typical recharge time	8 h

Battery life	2...3 year(s)
--------------	---------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25 cm
Package 1 Width	43 cm
Package 1 Length	19.7 cm
Package 1 Weight	6.5 kg
SCC14	10731304404498

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	232 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	62 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	168 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	E7333b0a-8d2c-4a40-a279-6eb5db3419eb
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Again



Repack and remanufacture

Recyclability potential, in %	62
End of life manual availability	End of Life Information
Removable battery	User replaceable
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



