


## Specifications



20535911

GV1G09

**EAN Code: 3389110212570**

|                                           |                                                 |
|-------------------------------------------|-------------------------------------------------|
| <b>Range</b>                              | Linery                                          |
| <b>Product name</b>                       | FT                                              |
| <b>Device short name</b>                  | GV1G                                            |
| <b>Product or component type</b>          | Terminal block                                  |
| <b>Accessory / separate part category</b> | Connection accessory                            |
| <b>Poles description</b>                  | 3P                                              |
| <b>Range compatibility</b>                | TeSys GV2<br>TeSys Deca<br>TeSys U<br>TeSys LS1 |

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ie] rated operational current | 63 A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Mounting location              | Top                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| IP degree of protection        | IP20 conforming to IEC 60529                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| [Ui] rated insulation voltage  | 690 V conforming to IEC 60947-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Connections - terminals        | Screw clamp terminals 1 cable(s) (4 AWG) - solid<br>Screw clamp terminals 1 cable(s) 1.5...16 mm² - flexible with cable end<br>Screw clamp terminals 1 cable(s) 1.5...16 mm² - flexible without cable end<br>Screw clamp terminals 1 cable(s) 1.5...25 mm² - solid<br>Screw clamp terminals 2 cable(s) 1.5...4 mm² - flexible with cable end<br>Screw clamp terminals 2 cable(s) 1.5...6 mm² - solid<br>Screw clamp terminals 2 cable(s) 1.5...4 mm² - flexible without cable end<br>Screw clamp terminals 1 cable(s) (4 AWG) - flexible |
| Tightening torque              | 1.7 N.m - on screw clamp terminals<br>2.2 N.m - on connector                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Product weight                 | 0.04 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

|                        |            |
|------------------------|------------|
| Product certifications | CE<br>UKCA |
|------------------------|------------|

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 4.500 cm |
| Package 1 Width              | 6.000 cm |
| Package 1 Length             | 7.000 cm |

|                              |           |
|------------------------------|-----------|
| Package 1 Weight             | 49.000 g  |
| Unit Type of Package 2       | S02       |
| Number of Units in Package 2 | 70        |
| Package 2 Height             | 15.000 cm |
| Package 2 Width              | 30.000 cm |
| Package 2 Length             | 40.000 cm |
| Package 2 Weight             | 3.706 kg  |
| Unit Type of Package 3       | P06       |
| Number of Units in Package 3 | 1120      |
| Package 3 Height             | 75.000 cm |
| Package 3 Width              | 60.000 cm |
| Package 3 Length             | 80.000 cm |
| Package 3 Weight             | 69.540 kg |

## Logistical informations

|                   |    |
|-------------------|----|
| Country of origin | RO |
|-------------------|----|

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 18 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better



### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

## Use Longer



### Lifetime extension

Repair

No

## Use Again



### Repack and remanufacture

End of life manual availability

[End of Life Information](#)

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Dimensions Drawings

Sets of Busbars GV2G... with Terminal Block GV1G09

