

Product datasheet

Specifications



TeSys GV4 - Auxiliary contact OF or SD for GV4

Local distributor code:
407813735 GV4AE11

EAN Code: 3606485444246

Main

Range	TeSys
Device short name	GV4AE
Product or component type	Auxiliary contact
Device application	Signalling
Range compatibility	TeSys TeSys GV4 TeSys TeSys BV4
Auxiliary contact composition	1 NO/NC
[Ue] rated operational voltage	<= 690 V
[Ith] conventional free air thermal current	5 A conforming to IEC 60947-5-1 5 A conforming to CSA C22.2 No 14 5 A conforming to UL 508
Mounting mode	Internal mounting

Complementary

[Ui] rated insulation voltage	690 V conforming to IEC 60947-1
[Ie] rated operational current	5 A <= 690 V AC-12 conforming to IEC 60947-5-1 5 A <= 48 V AC-15 conforming to IEC 60947-5-1 4 A 110/127 V AC-15 conforming to IEC 60947-5-1 3 A 220/240 V AC-15 conforming to IEC 60947-5-1 2.5 A 380...440 V AC-15 conforming to IEC 60947-5-1 0.11 A 660/690 V AC-15 conforming to IEC 60947-5-1 5 A <= 24 V DC-12 conforming to IEC 60947-5-1 2.5 A 48 V DC-12 conforming to IEC 60947-5-1 0.6 A 110/127 V DC-12 conforming to IEC 60947-5-1 0.3 A 250 V DC-12 conforming to IEC 60947-5-1 2.5 A <= 24 V DC-12 conforming to IEC 60947-5-1 1.2 A 48 V DC-12 conforming to IEC 60947-5-1 0.35 A 110/127 V DC-12 conforming to IEC 60947-5-1 0.05 A 250 V DC-12 conforming to IEC 60947-5-1 1 A <= 24 V DC-12 conforming to IEC 60947-5-1 0.2 A 48 V DC-12 conforming to IEC 60947-5-1 0.05 A 110/127 V DC-12 conforming to IEC 60947-5-1 0.03 A 250 V DC-12 conforming to IEC 60947-5-1
Rated power in VA	120 VA AC-12 at 24 V conforming to IEC 60947-5-1 240 VA AC-12 at 48 V conforming to IEC 60947-5-1 635 VA AC-12 at 110/127 V conforming to IEC 60947-5-1 1200 VA AC-12 at 230/240 V conforming to IEC 60947-5-1 2200 VA AC-12 at 380/440 V conforming to IEC 60947-5-1 3450 VA AC-12 at 660/690 V conforming to IEC 60947-5-1
Rated power in W	DC-12: 120 W 24 V conforming to IEC 60947-5-1 DC-12: 120 W 48 V conforming to IEC 60947-5-1 DC-12: 66 W 110 V conforming to IEC 60947-5-1 DC-12: 75 W 250 V conforming to IEC 60947-5-1
Associated fuse rating	5 A gG at 690 V conforming to IEC 60947-5-1
Minimum switching current	2 mA

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Minimum switching voltage	17 V
Mechanical durability	40000 cycles
Connections - terminals	Spring terminals 1 0.5...1.5 mm² - cable stiffness: flexible without cable end
Wire stripping length	8 mm

Environment

Quantity per set	Set of 1
------------------	----------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	8.000 cm
Package 1 Length	11.000 cm
Package 1 Weight	24.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4.000 cm
Package 2 Width	20.000 cm
Package 2 Length	27.000 cm
Package 2 Weight	269.000 g
Unit Type of Package 3	S03
Number of Units in Package 3	110
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	3.455 kg

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

EU RoHS Directive

[Compliant](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

Halogen-free status

Halogen free plastic parts product

PVC free

Yes

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

End of life manual availability

No need of specific recycling operations

Take-back

No

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Offer Marketing Illustration

Product benefits / Features

TeSys Deca Motor
Circuit Breakers
Technical Benefits



- Combines a circuit breaker and overload relay in a single device.
- Gives great detection accuracy, as well as alarming and advanced protections for refs.
- Magnetic, electronic thermal-magnetic, or electronic thermal magnetic versions with advanced protection.
- Patented EverLink creep-compensating technology.
- Spring-based system ensures a long lasting connection.
- Electronic core for high-accuracy, wide settings, dual motor class 10/20.