

Product datasheet

Specifications



High power contactor, TeSys Giga,
3 pole (3NO), AC-3 $\leq 440\text{V}$ 800A,
standard version, 100...250V wide
band AC/DC coil

LC1G800KUEN

EAN Code: 3606481922014

Main

Range	TeSys
Range of product	TeSys Giga
Product or component type	Contacteur
Device short name	LC1G
Contactor application	Power switching Motor control
Utilisation category	AC-1 AC-3 AC-3e AC-4 AC-5a AC-5b AC-6a AC-6b AC-8a AC-8b DC-1 DC-3 DC-5
Poles description	3P
[Ue] rated operational voltage	$\leq 1000\text{ V AC } 50/60\text{ Hz}$ $\leq 460\text{ V DC}$
[Ie] rated operational current	1050 A (at $<40\text{ }^{\circ}\text{C}$) at $\leq 1000\text{ V AC-1}$ 800 A (at $<60\text{ }^{\circ}\text{C}$) at $\leq 440\text{ V AC-3}$
[Uc] control circuit voltage	100...250 V AC 50/60 Hz 100...250 V DC
Control circuit voltage limits	Operational: 0.8 Uc Min...1.1 Uc Max (at $<60\text{ }^{\circ}\text{C}$) Drop-out: 0.1 Uc Max...0.45 Uc Min (at $<60\text{ }^{\circ}\text{C}$)

Complementary

[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	1050 A (at $40\text{ }^{\circ}\text{C}$)
Rated breaking capacity	5870 A at 440 V
[Icw] rated short-time withstand current	5.5 kA - 10 s 4.6 kA - 30 s 3.6 kA - 1 min 2.6 kA - 3 min 1.7 kA - 10 min
Associated fuse rating	800 A aM at $\leq 440\text{ V}$ for motor 630 A aM at $\leq 690\text{ V}$ for motor 1250 A gG at $\leq 690\text{ V}$ 1200 A UL Type L at $\leq 600\text{ V}$

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Average impedance	0.000065 Ohm
[Ui] rated insulation voltage	1000 V
Power dissipation per pole	70 W AC-1 - lth 1050 A 42 W AC-3 - lth 800 A
Compatibility code	LC1G
Pole contact composition	3 NO
Auxiliary contact composition	1 NO + 1 NC
Motor power kW	200 kW at 230 V AC 50/60 Hz (AC-3e) 335 kW at 400 V AC 50/60 Hz (AC-3e) 355 kW at 415 V AC 50/60 Hz (AC-3e) 375 kW at 440 V AC 50/60 Hz (AC-3e) 425 kW at 500 V AC 50/60 Hz (AC-3e) 560 kW at 690 V AC 50/60 Hz (AC-3e) 450 kW at 1000 V AC 50/60 Hz (AC-3e) 250 kW at 230 V AC 50/60 Hz (AC-3) 450 kW at 400 V AC 50/60 Hz (AC-3) 450 kW at 415 V AC 50/60 Hz (AC-3) 450 kW at 440 V AC 50/60 Hz (AC-3) 500 kW at 500 V AC 50/60 Hz (AC-3) 560 kW at 690 V AC 50/60 Hz (AC-3) 450 kW at 1000 V AC 50/60 Hz (AC-3) 200 kW at 230 V AC 50/60 Hz (AC-4) 375 kW at 400 V AC 50/60 Hz (AC-4) 355 kW at 415 V AC 50/60 Hz (AC-4) 375 kW at 440 V AC 50/60 Hz (AC-4) 400 kW at 500 V AC 50/60 Hz (AC-4) 475 kW at 690 V AC 50/60 Hz (AC-4) 400 kW at 1000 V AC 50/60 Hz (AC-4)
Motor power hp	300 hp at 200/208 V 60 Hz 350 hp at 230/240 V 60 Hz 700 hp at 460/480 V 60 Hz 800 hp at 575/600 V 60 Hz
Irms rated making capacity	7640 A at 440 V
Coil technology	Built-in bidirectional peak limiting
Safety reliability level	B10d = 100000 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 1800000 cycles contactor with mechanical load conforming to EN/ISO 13849-1
Mechanical durability	5 Mcycles
inrush power in VA (50/60 Hz, AC)	800 VA
inrush power in W (DC)	680 W
hold-in power consumption in VA (50/60 Hz, AC)	15.0 VA
hold-in power consumption in W (DC)	9.5 W
Operating time	40...70 ms closing 15...50 ms opening
Maximum operating rate	600 cyc/h AC-3 600 cyc/h AC-3e 300 cyc/h AC-1 150 cyc/h AC-4
Connections - terminals	Power circuit: bar 2 - busbar cross section: 52 x 20 mm Power circuit: lugs-ring terminals 1 185 mm² Power circuit: bolted connection Control circuit: push-in 1 0.2...2.5 mm² - cable stiffness: solid stranded without cable end Control circuit: push-in 1 0.25...2.5 mm² - cable stiffness: flexible with cable end Control circuit: push-in 2 0.5...1.0 mm² with cable end Control circuit: push-in 0.75...2.5 mm² - cable stiffness: solid stranded without cable end Control circuit: push-in 0.75...2.5 mm² - cable stiffness: flexible with cable end
Connection pitch	70 mm

Mounting support	Plate
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1 IEC 60335-1:Clause 30.2 IEC 60335-2-40:Annex JJ UL 60335-1 UL 60335-2-40:Annex JJ
Product certifications	CB Scheme CCC cULus EAC CE UKCA EU-RO-MR by DNV-GL
Tightening torque	58 N.m
Height	284 mm
Width	211 mm
Depth	266 mm
Product weight	14.2 kg

Environment

IP degree of protection	IP2X front face with shrouds conforming to IEC 60529 IP2X front face with shrouds conforming to VDE 0106
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-60...80 °C
Mechanical robustness	Vibrations 5...300 Hz 2 gn contactor open Vibrations 5...300 Hz 4 gn contactor closed Shocks 10 gn 11 ms contactor open Shocks 15 gn 11 ms contactor closed
Colour	Dark grey
Protective treatment	TH
Permissible ambient air temperature around the device	-40...70 °C at Uc

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.000 cm
Package 1 Width	34.500 cm
Package 1 Length	60.500 cm
Package 1 Weight	16.416 kg
Unit Type of Package 2	S06
Number of Units in Package 2	2
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	42.832 kg

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 893 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	134 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	24 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2 714 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	21 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	6fbdad13-bb7c-47d4-a6d6-d82dd6f54349
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Halogen free plastic parts product
PVC free	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	55
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Installation

Installation Videos

[TeSys Giga - How to install the auxiliary contact block](#)

[TeSys Giga - How to install and remove remote wear diagnosis module](#)

[TeSys Giga - How to install mechanical interlock kit](#)

[TeSys Giga - How to install cable memory kit](#)

[TeSys Giga - How to directly mount LR9G overload relay](#)

[TeSys Giga - How to replace control module](#)

[TeSys Giga - How to replace switching modules](#)

[TeSys Giga - How to assemble reverser solution](#)

[TeSys Giga - How to assemble change-over solution](#)

Offer Marketing Illustration

Product benefits / Features

A black TeSys Giga Contactor, model LC1G800KUEN, is shown against a green circular background. The device has a modular design with multiple terminals and a green label on the front.

TeSys Giga Contactors

Technical Benefits

- Self-diagnostic indicators and full-scale protection help speed up corrections and prevent downtime.
- Modular design that simplifies machine integration and maintenance.
- High power contactors (up to 800 A AC-3 or 1050 A AC-1) for AC/DC motor applications and AC/DC load applications.
- They can be used up to 1000 Vac power voltage and 460 Vdc power voltage.
- Ground fault protection, phase imbalance/failure protection, and protection of single-phase loads.
- The coil is designed for less energy consumption and wider voltage bandwidth.

Offer Marketing Illustration

Product benefits / Features



Offer Marketing Illustration

Product benefits / Features



TeSys Giga Contactors

Range Accessories



Mechanical Interlock



Cable memory kit



Terminal shroud



Auxiliary contact block



Remote Wear Diagnostic Module



Switching Module Kit



Control module



Phase separator



Change-over connection bar



Reverser connection bar

Offer Marketing Illustration

Product benefits / Features

TeSys Giga

Contactors



Simplified maintenance

A patented modular design for the switching and control unit and cable memory enables better performance and faster spare parts replacement in an optimised footprint.



Ready for critical applications

Improved auxiliary contacts (17 V/1 mA, 10-8) enable better reliability in harsh environments and conform to high-density PLC input applications.



Resilience and uptime

Self diagnostic functions enable predictive maintenance with easier and safer commissioning.

