


MG-CPMF



CERTIFICATIONS & APPROVALS

 UL (cURus)

Features

TECHNICAL INFORMATION

Minimum operating temperature	-30°C
Maximum operating temperature	60°C

MATERIAL COMPOSITION AND TREATMENTS

Material	Rigid PVC
Silicone-free	Yes

WEIGHT AND DIMENSIONS

Length	105mm
--------	-------

CLASSIFICATION AND DATA ORDERING

Customs code	39204910
--------------	----------

CERTIFICATIONS

Self-extinguishing fire class according to UL 94	V0
--	----

MG-CPMFA

tipo	Minimum application temperature [°c]	Maximum application temperature [°c]	Colour	Type of adhesive	Sheet elements	Number of lines	S [mm]	Width [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	UL 969 certification	EN ISO 4892-2
46940	-30	60	yellow	Acrylic-based adhesive	10	10	0.5	10	100	100	Yes	Yes	
46990	-30	60	white	Acrylic-based adhesive	10	10	0.5	10	100	100	Yes	Yes	Yes
43196N	-30	60	white	Acrylic-based adhesive	8	1	0.5	12	400	400	Yes	Yes	Yes
43146N	-30	60	yellow	Acrylic-based adhesive	8	1	0.5	12	400	400	Yes	Yes	

