


MG-SIGNS-VY



Features

TECHNICAL INFORMATION

Minimum operating temperature	-30°C
Maximum operating temperature	70°C
Minimum application temperature	10°C
Maximum application temperature	40°C
Type of adhesive	Acrylic-based adhesive

WEIGHT AND DIMENSIONS

Thickness	0.08mm
-----------	--------

MATERIAL COMPOSITION AND TREATMENTS

Silicone-free	Yes
---------------	-----

CLASSIFICATION AND DATA ORDERING

Customs code	39199080
--------------	----------



MG-SIGNS-VY

tipo	Colour	Sheet elements	Number of lines	Material	Width [mm]	ØI [mm]	ØE [mm]	L [mm]	Diameter [mm]	Height of the text box [mm]	Length of side of the triangle [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	UL 969 certification	EN ISO 4892-2
990101	yellow	12	4	PVC					25			600	600	Yes		
991102	yellow	1	1	PVC					100			50	50	Yes		
991103	yellow	4	2	PVC							50	200	200	Yes		
991104	yellow	4	2	PVC						15	50	200	200	Yes		
991105	yellow	1	1	PVC							100	50	50	Yes		
991106	yellow	1	1	PVC		22.5	62					50	50	Yes		
991107	yellow	1	1	PVC		22.5	90					50	50	Yes		
991108	yellow	1	1	PVC		30.5	90					50	50	Yes		
991109	yellow	2	1	PVC	37			74				100	100	Yes		
991110	yellow	2	1	PVC	52			105				100	100	Yes		
990860	white	12	4	PVC Film					25			600	600	Yes	Yes	Yes
990992	red	12	4	PVC					25			600	600	Yes		
990988	red	2	1	PVC	37			74				100	100			
990702	white	1	1	PVC Film					100			50	50	Yes	Yes	Yes
990825	white	2	1	PVC Film	52			105				100	100	Yes	Yes	Yes
990991	white	2	1	PVC Film	45			150				100	100	Yes	Yes	Yes