


MG-SPM



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40°C
Maximum operating temperature	130°C
Colour	white

WEIGHT AND DIMENSIONS

Horizontal pitch between the sheet elements	29mm
---	------

CERTIFICATIONS

EN 45545-2 certification	HL2
Self-extinguishing fire class according to UL 94	V0
Cembre internal test	Yes

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate
Silicone-free	Yes
Halogen free	Yes

CLASSIFICATION AND DATA ORDERING

Customs code	39269097
--------------	----------



MG-SPM-02

tipo	Sheet elements	Number of lines	S [mm]	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant
43291	12	3	0.8	7	20	360	360	Yes

MG-SPM-03

tipo	Sheet elements	Number of lines	S [mm]	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant
32291	12	3	1.4	9	19	360	360	Yes

MG-SPM-07

tipo	Sheet elements	Number of lines	S [mm]	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant
32690	20	5	1.4	3.3	12	600	600	Yes

MG-SPM-09

tipo	Sheet elements	Number of lines	S [mm]	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant
32895	12	3	1	8	20	360	360	Yes

MG-SPM-11

tipo	Sheet elements	Number of lines	S [mm]	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]
32995	24	6	1.1	7	12	720	720