


MG-TAP

TAGES FOR CABLES AND COMPONENTS, PRE-CUT, RIGID PVC



CERTIFICATIONS & APPROVALS



UL (cURus)

Features

TECHNICAL INFORMATION

Minimum operating temperature	-30°C
Maximum operating temperature	60°C

CLASSIFICATION AND DATA ORDERING

Customs code	39204910
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS

Material	Rigid PVC
Silicone-free	Yes

CERTIFICATIONS

Self-extinguishing fire class according to UL 94	V0
--	----



tipo	Colour	Sheet elements	Number of lines	S [mm]	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	UL 969 certification	CEI EN 60464-2	EN ISO 4892-2	DIN 30643	EN ISO 9227
47090N	white	42	6	0.5	15	17	1050	1050	Yes	Yes	Yes	Yes	Yes	Yes
47040N	yellow	42	6	0.5	15	17	1050	1050	Yes	Yes	Yes	Yes		Yes
47046	yellow	44	4	0.5	8.2	27	2200	11000	Yes	Yes	Yes	Yes		Yes
47047	yellow	20	4	0.5	18	27	1000	1000	Yes	Yes	Yes	Yes		Yes
47747	yellow	9	3	0.5	17.5	27	450	450		Yes	Yes	Yes		Yes
47020N	red	42	6	0.5	15	17	1050	1050	Yes		Yes	Yes		Yes
47010N	black	42	6	0.5	15	17	1050	1050	Yes		Yes	Yes		Yes
47060N	blue	42	6	0.5	15	17	1050	1050	Yes		Yes	Yes		Yes
47050N	green	42	6	0.5	15	17	1050	1050	Yes		Yes	Yes		Yes
47051NSGN	siemens green	28	4	0.5	15	27	1400	1400	Yes		Yes	Yes		Yes
47707GY	grey	9	3	0.5	17.5	27	450	450			Yes	Yes		Yes
47797	white	9	3	0.5	17.5	27	450	450		Yes	Yes	Yes	Yes	Yes
47091N	white	28	4	0.5	15	27	1400	4200	Yes	Yes	Yes	Yes	Yes	Yes
47794	white	12			0.5	27	600	600	Yes				Yes	
47795	white	28	4	0.5	15	27.7	1400	1400	Yes	Yes	Yes	Yes	Yes	Yes
47041N	yellow	28	4	0.5	15	27	1400	1400	Yes	Yes	Yes	Yes		Yes
47745	yellow	28	4	0.5	15	27.7	1400	1400	Yes	Yes	Yes	Yes		Yes
47705GY	grey	28	4	0.5	15	27.7	1400	1400	Yes		Yes	Yes		Yes
47704GY	grey	12			0.5	27	600	600	Yes					
47000NGY	grey	42	6	0.5	15	17	1050	1050	Yes		Yes	Yes		Yes
47001NGY	grey	28	4	0.5	15	27	1400	1400	Yes		Yes	Yes		Yes
47002NGY	grey	14	2	0.5	15	49	700	2100	Yes		Yes	Yes		Yes
47004GY	grey	24	4	0.5	17.5	27.8	1200	1200	Yes		Yes	Yes		Yes
47006GY	grey	44	4	0.5	8.2	27	2200	2200	Yes		Yes	Yes		Yes
47007GY	grey	20	4	0.5	18	27	1000	1000	Yes		Yes	Yes		Yes
47700GY	grey	56	4	0.5	6.4	27.3	1400	1400	Yes		Yes	Yes		Yes
47701GY	grey	24	4	0.5	16.3	27.3	1200	1200	Yes		Yes	Yes		Yes
47021N	red	28	4	0.5	15	27	1400	1400	Yes		Yes	Yes		Yes
47011N	black	28	4	0.5	15	27	1400	1400	Yes		Yes	Yes		Yes

tipo	Colour	Sheet elements	Number of lines	S [mm]	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	UL 969 certification	CEI EN 60464-2	EN ISO 4892-2	DIN 30643	EN ISO 9227
47051N	green	28	4	0.5	15	27	1400	1400	Yes		Yes	Yes		Yes
47061N	blue	28	4	0.5	15	27	1400	1400	Yes		Yes	Yes		Yes
47003GY	grey	14	2	0.5	15	67	350	350	Yes		Yes	Yes		Yes
47013	black	14	2	0.5	15	67	350	350	Yes		Yes	Yes		Yes
47092N	white	14	2	0.5	15	49	700	2100	Yes	Yes	Yes	Yes	Yes	Yes
47042N	yellow	14	2	0.5	15	49	700	700	Yes	Yes	Yes	Yes		Yes
47022N	red	14	2	0.5	15	49	700	700	Yes		Yes	Yes		Yes
47012N	black	14	2	0.5	15	49	700	2100	Yes		Yes	Yes		Yes
47062N	blue	14	2	0.5	15	49	700	700	Yes		Yes	Yes		Yes
47052N	green	14	2	0.5	15	49	700	700	Yes		Yes	Yes		Yes
47093	white	14	2	0.5	15	67	350	1050	Yes	Yes	Yes	Yes	Yes	Yes
47043	yellow	14	2	0.5	15	67	350	350	Yes	Yes	Yes	Yes		Yes
47023	red	14	2	0.5	15	67	350	350	Yes		Yes	Yes		Yes
47063	blue	14	2	0.5	15	67	350	350	Yes		Yes	Yes		Yes
47053	green	14	2	0.5	15	67	350	350	Yes		Yes	Yes		Yes
47094	white	24	4	0.5	17.5	27.8	1200	1200	Yes	Yes	Yes	Yes	Yes	Yes
47014	black	24	4	0.5	17.5	27.8	1200	1200	Yes		Yes	Yes		Yes
47016	black	44	4	0.5	8.2	27	2200	2200	Yes		Yes	Yes		Yes
47026	red	44	4	0.5	8.2	27	2200	11000	Yes		Yes	Yes		Yes
47096	white	44	4	0.5	8.2	27	2200	2200	Yes	Yes	Yes	Yes	Yes	Yes
47017	black	20	4	0.5	18	27	1000	1000	Yes		Yes	Yes		Yes
47027	red	20	4	0.5	18	27	1000	5000	Yes		Yes	Yes		Yes
47097	white	20	4	0.5	18	27	1000	1000	Yes	Yes	Yes	Yes	Yes	Yes
47098	white	21	3	0.5	15	32	1050	1050	Yes	Yes	Yes	Yes	Yes	Yes
47198	white	14	2	0.5	15	43	700	700	Yes	Yes	Yes	Yes	Yes	Yes
47790	white	56	4	0.5	6.4	27.3	1400	1400	Yes	Yes	Yes	Yes	Yes	Yes
47791	white	24	4	0.5	16.3	27.3	1200	1200	Yes	Yes	Yes	Yes	Yes	Yes