


MG-TAPW

TAGES FOR CABLES AND COMPONENTS, PRE-CUT, RIGID PVC



CERTIFICATIONS & APPROVALS



UL (cURus)

Features

TECHNICAL INFORMATION

Minimum operating temperature	-30°C
Maximum operating temperature	60°C

WEIGHT AND DIMENSIONS

Thickness	0.5mm
Width	9mm

CERTIFICATIONS

Self-extinguishing fire class according to UL 94	V0
Cembre internal test	Yes
CEI EN 61010-1 ed.2	Yes
CEI 16-7	Yes
DIN 30643	Yes

MATERIAL COMPOSITION AND TREATMENTS

Material	Rigid PVC
Silicone-free	Yes

CLASSIFICATION AND DATA ORDERING

Customs code	39204910
--------------	----------



MG-TAPW

tipo	Colour	Sheet elements	Number of lines	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	UL 969 certification	EN ISO 4892-2
49090N	white	55	5	20	2750	8250	Yes	Yes	Yes
49040N	yellow	55	5	20	2750	2750	Yes	Yes	
49042N	yellow	88	8	12	2200	2200	Yes	Yes	
49043N	yellow	77	7	15	1925	1925	Yes	Yes	
49044	yellow	20	2	50	1000	1000	Yes	Yes	
49045N	yellow	11	1	70	550	550	Yes	Yes	
49091N	white	33	3	35	1650	1650	Yes	Yes	Yes
49093N	white	77	7	15	1925	1925	Yes	Yes	Yes
49094	white	20	2	50	1000	1000	Yes	Yes	Yes
49092N	white	88	8	12	2200	2200	Yes	Yes	Yes
49041N	yellow	33	3	35	1650	1650	Yes	Yes	
49095N	white	11	1	70	550	550	Yes	Yes	Yes
49046	yellow	30	3	29	1500	1500	Yes	Yes	
49066	blue	30	3	29	1500	7500	Yes		
49053N	green	77	7	15	1925	9625	Yes		
49055N	green	11	1	70	550	550	Yes		
49096	white	30	3	29	1500	1500	Yes	Yes	Yes