


MG-TDM



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40°C
Maximum operating temperature	130°C

WEIGHT AND DIMENSIONS

Width	4mm
-------	-----

CERTIFICATIONS

ROHS compliant	Yes
Self-extinguishing fire class according to UL 94	V0
Cembre internal test	Yes
DIN 30643	Yes

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate
Silicone-free	Yes
Halogen free	Yes

CLASSIFICATION AND DATA ORDERING

Customs code	39269097
--------------	----------



MG-TDM-01		Range of cable cross section [mm²]			Ø [mm]			
		0.5			1.6			
tipo	Colour	Sheet elements	Number of lines	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	EN 45545-2 certification (r23)	EN 45545-2 certification (r22)
40190	white	66	6	12	1320	1320		HL2
40191	white	40	4	16	800	800		HL2
40192	white	40	4	12	800	800		HL2
40142	yellow	40	4	12	800	800	HL3	HL3
40140	yellow	66	6	12	1320	1320	HL3	HL3
40141	yellow	40	4	16	800	800	HL3	HL3

MG-TDM-02		Range of cable cross section [mm²]			Ø [mm]			
		1			2			
tipo	Colour	Sheet elements	Number of lines	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	EN 45545-2 certification (r23)	EN 45545-2 certification (r22)
40290	white	66	6	12	1056	1056		HL2
40291	white	40	4	16	640	640		HL2
40292	white	40	4	12	640	640		HL2
40242	yellow	40	4	12	640	640	HL3	HL3
40240	yellow	66	6	12	1056	1056	HL3	HL3
40241	yellow	40	4	16	640	640	HL3	HL3