


MG-TDMO



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40°C
Maximum operating temperature	130°C
Sheet elements	40
Number of lines	4

WEIGHT AND DIMENSIONS

Width	4mm
-------	-----

CERTIFICATIONS

Self-extinguishing fire class according to UL 94	V0
Cembre internal test	Yes
DIN 30643	Yes

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate
Silicone-free	Yes
Halogen free	Yes

CLASSIFICATION AND DATA ORDERING

Customs code	39269097
--------------	----------



MG-TDMO-01		Range of cable cross section [mm²]		Ø [mm]			
		0.5		2			
tipo	Colour	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN 45545-2 certification (r22)	EN 45545-2 certification (r23)
40390	white	12	880	880	Yes	HL2	
40391	white	16	880	880	Yes	HL2	
40340	yellow	12	880	880	Yes	HL3	HL3
40341	yellow	16	880	880	Yes	HL3	HL3

MG-TDMO-02		Range of cable cross section [mm²]		Ø [mm]			
		1.5		2.9			
tipo	Colour	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN 45545-2 certification (r23)	EN 45545-2 certification (r22)
40491	white	16	640	640	Yes		HL2
40490	white	12	640	640	Yes		HL2
40441	yellow	16	640	640	Yes	HL3	HL3
40440	yellow	12	640	640	Yes	HL3	HL3

MG-TDMO-03		Range of cable cross section [mm²]		Ø [mm]			
		4		4			
tipo	Colour	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN 45545-2 certification (r23)	EN 45545-2 certification (r22)
40591	white	16	560	560	Yes		HL2
40590	white	12	560	560	Yes		HL2
40541	yellow	16	560	560	Yes	HL3	HL3
40540	yellow	12	560	560	Yes	HL3	HL3