


MG-TPM



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40°C
Maximum operating temperature	130°C
Sheet elements	45
Number of lines	4

WEIGHT AND DIMENSIONS

Thickness	1.4mm
Width	4mm

CLASSIFICATION AND DATA ORDERING

Customs code	39206100
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate
Silicone-free	Yes
Halogen free	Yes

LOGISTIC

Unit in minimal packaging	2250PCE
Unit in standard packaging	2250PCE

CERTIFICATIONS

ROHS compliant	Yes
Self-extinguishing fire class according to UL 94	V0
Cembre internal test	Yes
CEI EN 60950-1	Yes
CEI EN 61010-1 ed.2	Yes

MG-TPM

tipo	Colour	L [mm]	EN 45545-2 certification (r22)	EN 45545-2 certification (r23)	EN ISO 4892-2
40090	white	10	HL2		Yes
40091	white	12	HL2		Yes
40040	yellow	10	HL3	HL3	
40041	yellow	12	HL3	HL3	
40092	white	15	HL2		Yes
40093	white	18	HL2		Yes
40042	yellow	15	HL3	HL3	
40043	yellow	18	HL3	HL3	



