


MG-TPMF

CABLE TAGS, FLAT SERIES, PRE-CUT, FOR PMF HOLDERS, RIGID PVC



CERTIFICATIONS & APPROVALS



UL (cURus)

Features

TECHNICAL INFORMATION

Minimum operating temperature	-30°C
Maximum operating temperature	60°C

WEIGHT AND DIMENSIONS

Thickness	0.5mm
Width	4mm

CERTIFICATIONS

Self-extinguishing fire class according to UL 94	V0
Cembre internal test	Yes
CEI EN 60464-2	Yes
CEI EN 60950-1	Yes
CEI EN 61010-1 ed.2	Yes
EN ISO 4892-2	Yes
CEI 16-7	Yes
EN ISO 9227	Yes
UNI EN ISO 175	Yes

MATERIAL COMPOSITION AND TREATMENTS

Material	Rigid PVC
Silicone-free	Yes

CLASSIFICATION AND DATA ORDERING

Customs code	39204910
--------------	----------



MG-TPMF

tipo	Colour	Sheet elements	Number of lines	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	UL 969 certification
42096B	white	48	3	30	1200	3600	Yes	Yes
42046B	yellow	48	3	30	1200	3600	Yes	Yes
42026B	red	48	3	30	1200	1200	Yes	
42056B	green	48	3	30	1200	1200	Yes	
42066B	blue	48	3	30	1200	1200	Yes	
42063B	blue	64	4	20	1600	1600	Yes	
42023B	red	64	4	20	1600	1600	Yes	
42053B	green	64	4	20	1600	1600	Yes	
42071B	purple	80	5	12	4000	4000		
42013B	black	64	4	20	1600	1600	Yes	
42090B	white	112	7	10	5600	16800	Yes	Yes
42091B	white	80	5	12	4000	12000	Yes	Yes
42092B	white	80	5	15	4000	12000	Yes	Yes
42060B	blue	112	7	10	5600	5600	Yes	
42050B	green	112	7	10	5600	5600	Yes	
42010B	black	112	7	10	5600	5600	Yes	
42040B	yellow	112	7	10	5600	16800	Yes	
42041B	yellow	80	5	12	4000	4000	Yes	Yes
42042B	yellow	80	5	15	4000	12000	Yes	Yes
42020B	red	112	7	10	5600	5600	Yes	
42001BGY	grey	80	5	12	4000	4000	Yes	
42000BGY	grey	112	7	10	5600	5600	Yes	
42010N	black	112	7	10	5600	5600	Yes	
42011B	black	80	5	12	4000	4000	Yes	
42021B	red	80	5	12	4000	4000	Yes	
42061B	blue	80	5	12	4000	4000	Yes	
42051B	green	80	5	12	4000	4000	Yes	
42097B	white	32	2	40	800	800	Yes	Yes
42047B	yellow	32	2	40	800	2400	Yes	Yes
42093B	white	64	4	20	1600	4800	Yes	Yes

tipo	Colour	Sheet elements	Number of lines	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	UL 969 certification
42043B	yellow	64	4	20	1600	4800	Yes	Yes
42094B	white	64	4	18	1600	1600	Yes	Yes
42044B	yellow	64	4	18	1600	1600	Yes	Yes