


MG-VRT-A-HF

ADHESIVE PANEL PLATES, PRE-CUT, POLYCARBONATE, HALOGEN FREE



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40°C
Maximum operating temperature	120°C
Minimum application temperature	10°C
Maximum application temperature	40°C
Type of adhesive	Acrylic-based adhesive

WEIGHT AND DIMENSIONS

Thickness	0.5mm
-----------	-------

CERTIFICATIONS

ROHS compliant	Yes
Self-extinguishing fire class according to UL 94	V0
EN ISO 4892-2	Yes

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate
Silicone-free	Yes
Halogen free	Yes

CLASSIFICATION AND DATA ORDERING

Customs code	39199080
--------------	----------



MG-VRT-A-HF

tipo	Colour	Sheet elements	Number of lines	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	EN 45545-2 certification (r22)
88908-HF	white	4	1	25	80	80	25	100	100	HL2
88904-HF	white	1	1	105	110	110	105	25	25	HL2
88903-HF	white	2	1	52	107	107	52	50	50	HL2
88928-HF	white	1	1	102	138	138	102	25	25	HL2
88901-HF	white	2	1	42	78	78	42	50	150	HL2
88701-HF	metallic grey	2	1	42	78	78	42	50	50	
88702-HF	metallic grey	1	1	62	88	88	62	25	25	
88769-HF	metallic grey	2	1	50	100	100	50	50	150	
88777-HF	metallic grey	1	1	100	140	140	100	25	75	
88762-HF	metallic grey	2	2	60	100	100	60	50	150	
88703-HF	metallic grey	2	1	52	107	107	52	50	50	
88735-HF	metallic grey	2	1	40	138	138	40	50	50	
88771-HF	metallic grey	2	2	57	82.5	82.5	57	50	50	
88765-HF	metallic grey	5	1	20	110	110	20	125	125	
88704-HF	metallic grey	1	1	105	110	110	105	25	25	
88717-HF	metallic grey	3	1	35	100	100	35	75	75	
88708-HF	metallic grey	4	1	25	80	80	25	100	100	
88716-HF	metallic grey	8	2	25	50	50	25	200	200	
88713-HF	metallic grey	1	1	92	118	118	92	25	25	
88728-HF	metallic grey	1	1	102	138	138	102	25	75	
88700N-HF	metallic grey	6	2	32	58	58	32	150	450	

