


MG-VRT-A

ADHESIVE PANEL PLATES, PRE-CUT, RIGID PVC



CERTIFICATIONS & APPROVALS



UL (cURus)

Features

TECHNICAL INFORMATION

Minimum operating temperature	-30°C
Maximum operating temperature	60°C
Minimum application temperature	10°C
Maximum application temperature	40°C
Type of adhesive	Acrylic-based adhesive

CLASSIFICATION AND DATA ORDERING

Customs code	39199080
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS

Material	Rigid PVC
Silicone-free	Yes

CERTIFICATIONS

Self-extinguishing fire class according to UL 94	V0
Cembre internal test	Yes
CEI EN 60950-1	Yes
CEI EN 61010-1 ed.2	Yes
EN ISO 4892-2	Yes
CEI 16-7	Yes
EN ISO 9227	Yes



tipo	Colour	Sheet elements	Number of lines	S [mm]	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	UL 969 certification
88655	blue	7	1	0.5	15	102	102	15	175	175	Yes	
88628	blue	1	1	0.5	102	138	138	102	25	25	Yes	
88613	blue	1	1	0.5	92	118	118	92	25	25	Yes	
88603	blue	2	1	0.5	52	107	107	52	50	50	Yes	
88616	blue	8	2	0.5	25	50	50	25	200	200	Yes	
88617	blue	3	1	0.5	35	100	100	35	75	75	Yes	
88605	blue	4	1	0.5	25	100	100	25	100	100	Yes	
88900N	white	6	2	0.5	32	58	58	32	150	150	Yes	Yes
88608	blue	4	1	0.5	25	80	80	25	100	100	Yes	
88973	white	5	5	0.5	20	127	127	20	125	125	Yes	Yes
88945	white	3	1	0.5	35	75	75	35	75	375	Yes	Yes
88601	blue	2	1	0.5	42	78	78	42	50	50	Yes	
88901	white	2	1	0.5	42	78	78	42	50	50	Yes	Yes
88902	white	1	1	0.5	62	88	88	62	25	25	Yes	Yes
88971	white	2	2	0.5	57	82.5	82.5	57	50	50	Yes	Yes
88903	white	2	1	0.5	52	107	107	52	50	150	Yes	Yes
88962	white	2	2	0.5	60	100	100	60	50	50	Yes	Yes
88963	white	1	1	0.5	65	122	122	65	25	25	Yes	Yes
88964	white	1	1	0.5	90	140	140	90	25	25	Yes	Yes
88235	red	2	1	0.5	40	138	138	40	50	50	Yes	
88228	red	1	1	0.5	102	138	138	102	25	25	Yes	
88946	white	4	1	0.5	25	140	140	25	100	100	Yes	Yes
88935	white	2	1	0.5	40	138	138	40	50	50	Yes	Yes
88928	white	1	1	0.5	102	138	138	102	25	25	Yes	Yes
88904	white	1	1	0.5	105	110	110	105	25	25	Yes	Yes
88005	black	4	1	0.5	25	100	100	25	100	100	Yes	
88918	white	4	2	0.5	50	50	50	50	100	100	Yes	Yes
88905	white	4	1	0.5	25	100	100	25	100	100	Yes	Yes
88917	white	3	1	0.5	35	100	100	35	75	75	Yes	Yes
88908	white	4	1	0.5	25	80	80	25	100	100	Yes	Yes

tipo	Colour	Sheet elements	Number of lines	S [mm]	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	UL 969 certification
88913	white	1	1	0.5	92	118	118	92	25	25	Yes	Yes
88916	white	8	2	0.5	25	50	50	25	200	200	Yes	Yes
88400N	yellow	6	2	0.5	32	58	58	32	150	450	Yes	Yes
88446	yellow	4	1	0.5	25	140	140	25	100	100	Yes	Yes
88401	yellow	2	1	0.5	42	78	78	42	50	50	Yes	Yes
88473	yellow	5	5	0.5	20	127	127	20	125	125		Yes
88402	yellow	1	1	0.5	62	88	88	62	25	25	Yes	Yes
88116	black	8	2	0.5	25	50	50	25	200	200	Yes	
88403	yellow	2	1	0.5	52	107	107	52	50	50	Yes	Yes
88101	black	2	1	0.5	42	78	78	42	50	50	Yes	
88000N	black	6	2	0.5	32	58	58	32	150	450	Yes	
88103	black	2	1	0.5	52	107	107	52	50	150	Yes	
88128	black	1	1	0.5	102	138	138	102	25	25	Yes	
88113	black	1	1	0.5	92	118	118	92	25	25	Yes	
88118	black	4	2	0.5	50	50	50	50	100	1000	Yes	
88108	black	4	1	0.5	25	80	80	25	100	100	Yes	
88135	black	2	1	0.5	40	138	138	40	50	50	Yes	
88404	yellow	1	1	0.5	105	110	110	105	25	25	Yes	Yes
88428	yellow	1	1	0.5	102	138	138	102	25	25	Yes	Yes
88445	yellow	3	1	0.5	35	75	75	35	75	75	Yes	Yes
88408	yellow	4	1	0.5	25	80	80	25	100	100	Yes	Yes
88405	yellow	4	1	0.5	25	100	100	25	100	100	Yes	Yes
88413	yellow	1	1	0.5	92	118	118	92	25	25	Yes	Yes
88416	yellow	8	2	0.5	25	50	50	25	200	200	Yes	Yes
88417	yellow	3	1	0.5	35	100	100	35	75	75	Yes	Yes
88418	yellow	4	2	0.5	50	50	50	50	100	100	Yes	Yes
88800	metallic grey	6	2		58	32	58	32	75	75	Yes	
88462	yellow	2	2	0.5	60	100	100	60	50	50	Yes	Yes
88803	metallic grey	6	2		58	32	58	32	50	50	Yes	
88007	black	3	1	0.5	35	100	100	35	75	750	Yes	
88762GY	grey	2	2	0.5	60	100	100	60	50	50	Yes	

tipo	Colour	Sheet elements	Number of lines	S [mm]	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	UL 969 certification
88735GY	grey	2	1	0.5	40	138	138	40	50	50	Yes	
88717GY	grey	3	1	0.5	35	100	100	35	75	75	Yes	
88728GY	grey	1	1	0.5	102	138	138	102	25	75	Yes	
88716GY	grey	8	2	0.5	25	50	50	25	200	200	Yes	
88701GY	grey	2	1	0.5	42	78	78	42	50	50	Yes	
88702GY	grey	1	1	0.5	62	88	88	62	25	25	Yes	
88703GY	grey	2	1	0.5	52	107	107	52	50	50	Yes	
88713GY	grey	1	1	0.5	92	118	118	92	25	25	Yes	
88704GY	grey	1	1	0.5	105	110	110	105	25	75	Yes	
88700NGY	grey	6	2	0.5	32	58	58	32	150	150	Yes	
88708GY	grey	4	1	0.5	25	80	80	25	100	100	Yes	
88771GY	grey	2	2	0.5	57	82.5	82.5	57	50	50	Yes	
88200N	red	6	2	0.5	32	58	58	32	150	150	Yes	
88216	red	8	2	0.5	25	50	50	25	200	200	Yes	
88217	red	3	1	0.5	35	100	100	35	75	75	Yes	
88203	red	2	1	0.5	52	107	107	52	50	50	Yes	
88205	red	4	1	0.5	25	100	100	25	100	100	Yes	
88208	red	4	1	0.5	25	80	80	25	100	400	Yes	
88213	red	1	1	0.5	92	118	118	92	25	25	Yes	
88204	red	1	1	0.5	105	110	110	105	25	25	Yes	
88201	red	2	1	0.5	42	78	78	42	50	50	Yes	
88516	green	8	2	0.5	25	50	50	25	200	200	Yes	
88517	green	3	1	0.5	35	100	100	35	75	225	Yes	
88745GY	grey	3	1	0.5	35	75	75	35	75	75	Yes	
88600N	blue	6	2	0.5	32	58	58	32	150	150	Yes	