

Product datasheet

Specifications



ClimaSys CC - thermostat 250V - range of temperature +5...60°C - 1 NO/NC - °C

Local distributor code:
388826922

NSYCCOTHI

EAN Code: 3606480152559

Main

Range	ClimaSys
Product name	ClimaSys CC
Product or component type	Thermostat
Temperature setting range	5...60 °C
Information displayed	Temperature in °C

Complementary

Input voltage	240 V
Sensor type	Bimetal
Contacts type and composition	1 NO/NC
Contact resistance	10 mOhm
Service life in cycles	100000 cycles
Maximum switching capacity	4 A 250 V AC inductive pf: 0.6 30 W DC 10 A 250 V AC inductive
Electrical connection	4 terminals, clamping capacity: 2.5 mm²
Mounting mode	Clipped
Height	External: 68 mm
Width	External: 56 mm
Depth	External : 44 mm
Product weight	100 g
Mounting location	Cross rails On mounting plate 35 mm DIN rail Spacial upright
Ambient air temperature for operation	-20...80 °C
IP degree of protection	IP20
Hysteresis	7 K +/- 0.4K
Number of outputs	1 heating function 1 ventilation function
Material	PC
Colour	Light grey
Flame retardance	Self-extinguishing conforming to UL94 (material V0)
Product certifications	UL

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.000 cm
Package 1 Width	7.000 cm
Package 1 Length	8.000 cm
Package 1 Weight	84.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	75
Package 2 Height	26.000 cm
Package 2 Width	41.500 cm
Package 2 Length	32.500 cm
Package 2 Weight	7.428 kg
Unit Type of Package 3	P12
Number of Units in Package 3	3000
Package 3 Height	198.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	311.000 kg

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	3452f1a3-f13d-4adf-84ba-2572bcc8e35c
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
PVC free	Yes
Silicone-free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins