

Product datasheet

Specifications



Side Connected Cooling Unit, Climasys CU, 3200W, 230V, 50/60Hz, IP55

NSYCU3K2DG

EAN Code: 3606486055274

Main

Range	ClimaSys
Product name	CU
mounting type	Side
Product or component type	Cooling unit
Installation	Indoor side
Product destination	For enclosure
mounting mode	By screws
Supply Voltage	220...240 V 1 phase 50 Hz EN/IEC 230 V +/- 6 % 1 phase 60 Hz UL
Rated Power	3180 W
Cooling power	3180 W 50/60 Hz L35-L35 2370 W 50/60 Hz L35-L50

Complementary

Height	1300 mm
Width	490 mm
Depth	250 mm
[In] rated current	5.6 A
Inrush current	30 A
Power consumption in W	1236 W at 50/60 Hz, L35-L35 1410 W at 50/60 Hz, L35-L50
Energy efficiency ratio	2.6
Control type	Electronic controller
Temperature setting range	20...50 °C at 50/60 Hz
Ambient air temperature for operation	20...50 °C at 50/60 Hz inside the enclosure: 5...55 °C at 50/60 Hz outside the enclosure:
Noise level	77 dB
Pressure	32 bar
Flow rate	Internal circuit: 1200 m3/h at 50/60 Hz External circuit: 1400 m3/h at 50/60 Hz
Product weight	58.9 kg
Cooling gas type	R513a (0.482 kg)
Type of filter	Optional external circuit filter
Recommended circuit breaker protection	M9F23116

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Thermal protection Recommended (fuse)	15 A (T)
Material	Steel
Colour	Grey (RAL 7035)

Environment

Product certifications	UL IEC EN
Directives	2006/42/EC - machinery 2014/30/EU - electromagnetic compatibility 2011/65/EU - RoHS
Standards	EN/ISO 12100 EN 60335-1 EN 60335-2-40 EN 61000-3-2 EN 61000-3-3 EN 61000-6-2 EN 61000-6-3 EN/IEC 63000:2018 EN 14511
IP degree of protection	IP55 conforming to IEC 60529 (on the internal circuit) IP24 conforming to IEC 60529 (on the external circuit)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.500 cm
Package 1 Width	52.000 cm
Package 1 Length	144.000 cm
Package 1 Weight	64.600 kg
Unit Type of Package 2	P12
Number of Units in Package 2	2
Package 2 Height	166.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	164.200 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	3 550 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	244 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	6 kg CO2 eq.
Carbon footprint of the installation phase [A5]	9 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3 166 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	125 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
F-gas free	Product containing F-gas
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Again

 Repack and remanufacture	
Recyclability potential, in %	89
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative











