

Product datasheet

Specifications



Multi-fixing LED lamp without socket - 230 V AC - 10W - presence detection

NSYLAMLDD

EAN Code: 3606481203113

Main

Range of product	Lighting and power sockets
Accessory / separate part category	Lighting accessory
Product or component type	Lamp
Device application	Multi-purpose
Device composition	1 lamp 1 fixing elements
Power factor	0.9

Complementary

Outlet standard deviation	Without socket
Rated lamp wattage	10 W
[Ue] rated operational voltage	120/230 V AC 50/60 Hz
Bulb base	Integral LED
Bulb type	LED
Control type	Built-it switch Movement sensor
Luminous flux	950 lm
Colour temperature	4000 K
Service life in hours	25000 h
Electrical connection	Cable quick connector 3 m not supplied Cable quick connector 1 m not supplied
Mounting support	Bracket Metal parts DIN rail
fixing mode	Magnetic fixing Clip-in Screws
Range compatibility	Spacial PanelSeT
Material	PC (UL94 V-0)
Length	372 mm
Height	63 mm
Width	40 mm
Colour	Black (RAL 9005)

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

IP degree of protection	IP20 conforming to IEC 60529
Electrical insulation class	Class II
Electromagnetic compatibility	EMC immunity conforming to EN 55015
Standards	UL 508 A IEC 60598 UL 8750 UL 1598 EN 55015 UL 94
Ambient air temperature for operation	-16...65 °C
Ambient air temperature for storage	-10...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.000 cm
Package 1 Width	5.000 cm
Package 1 Length	40.000 cm
Package 1 Weight	816.000 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	31.500 cm
Package 2 Width	42.000 cm
Package 2 Length	18.000 cm
Package 2 Weight	8.630 kg
Unit Type of Package 3	PAM
Number of Units in Package 3	110
Package 3 Height	52.000 cm
Package 3 Width	100.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	110.000 kg

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	60 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	8 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	51 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
PVC free	Yes
Silicone-free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	36
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins