

Product datasheet

Specifications



Floor standing enclosure polyester vers.PLA completely sealed 1000x500x420 IP65

Local distributor code:

403419625

NSYPLA1054G

EAN Code: 3606480774454

Main

Range	PanelSeT
Product name	PanelSeT PLA
Enclosure type	Multi-purpose
Product or component type	Suitable enclosure
Version	PLA
Nominal height	1000 mm
Nominal width	500 mm
Nominal depth	420 mm
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part 2 side part 1 rear panel 1 door

Complementary

Body type	Sealed top and bottom part assembled with side parts
Door type	Plain front
Number of doors	1 door(s)
Door opening side	Reversible (120 °)
Lock type	4 points lock, 5 mm double-bar
Accessibility for operation	Front Rear
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)
Standards	IEC 62208 UL 508 A
NEMA degree of protection	NEMA 5 NEMA 13 NEMA 3X NEMA 2 NEMA 3R NEMA 3 NEMA 12 NEMA 1 NEMA 3S

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	Veritas DNV Marine UL/cUL listed
Electrical insulation class	Class II

Environment

IP degree of protection	IP65 conforming to IEC 60529 (completely sealed)
IK degree of protection	IK10 conforming to IEC 62262 (plain door)
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for storage	-35...90 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	100.000 cm
Package 1 Width	53.000 cm
Package 1 Length	47.500 cm
Package 1 Weight	24.750 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	4
Package 2 Height	115.000 cm
Package 2 Width	100.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	111.500 kg

Logistical informations

Country of origin	ES
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	193 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	90 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	49 kg CO2 eq.
Carbon footprint of the installation phase [A5]	8 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	45 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	1341ad4e-77b9-40e3-bab0-32043fbc5959
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	6
End of life manual availability	No need of specific recycling operations
Take-back	No

Image of product in real life situation

