



PRODUCT-DETAILS

OT16G1-4MSN2

OT16G1-4MSN2 SWITCH DISCONNECTOR



General Information	
Extended Product Type:	OT16G1-4MSN2
Product ID:	1SCA163385R1001
EAN:	6417019930923
Catalog Description:	OT16G1-4MSN2 SWITCH DISCONNECTOR
Long Description:	OT Plus Switch disconnecter series. 4-pole front operated base mounted DIN-rail mountable switch disconnecter suitable for panels with 45mm DIN cut-out. The switch disconnecter has inbuilt screw terminals and comes with direct-mounted knob handle that can be padlocked.
Display Name:	OT16G1-4MSN2

ABB EcoSolutions	
ABB EcoSolutions:	Yes
ABB Site Meeting Group Waste To Landfill Target:	No non-hazardous waste is sent to a landfill UL 2799 Zero Waste To Landfill Validation available
End Of Life Disassembling Instructions:	1SCC301152M0201
Environmental Product Declaration - EPD:	1SCC301349D0201
Extended Product Lifetime:	Product Durability

Improved Energy Efficiency for Customers:	Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line
Recyclability Rate of the Product acc. to EN45555:	Design for Closing Resource Loops - Standard EN45555 - 92.5 %
Sustainable Material Content in Packaging (wt. %):	FSC 100% Cardboard - 35.9 % FSC 100% Cardboard - 41.98 % FSC 100% Cardboard - 22.12 %

Material Compliance

Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	1SCC011021D0201
RoHS Declaration:	1SCC011020D0201
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA:	1SCC011025D0201

Popular Downloads

Instructions and Manuals:	1SCC301149M0201
Mechanical Drawings:	OT16_63G1_4M_N2_SR.STP

Environmental

Degree of Protection:	Front IP20
Pollution Degree:	3

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85363030
Country of Origin:	Finland

Dimensions

Product Net Width:	46 mm
Product Net Height:	68 mm
Product Net Depth / Length:	74 mm
Product Net Weight:	0.166 kg

Container Information

Package Level 1 Units:	box 1 piece
------------------------	-------------

Package Level 1 Width:	48 mm
Package Level 1 Depth / Length:	71 mm
Package Level 1 Height:	74 mm
Package Level 1 Gross Weight:	0.189 kg
Package Level 1 EAN:	6417019930923
Package Level 2 Units:	carton 10 piece
Package Level 2 Width:	91 mm
Package Level 2 Depth / Length:	298 mm
Package Level 2 Height:	170 mm
Package Level 2 Gross Weight:	1.89 kg

Technical

Connecting Capacity Main Circuit:	Flexible with Ferrule 1/2x Cu 0.75...4 mm ² Solid 1/2x Cu 0.75...6 mm ² Flexible 1x Cu 1.5...16 mm ² Flexible 2x Cu 1.5...6 mm ² Stranded 1x Cu 1.5...16 mm ² Stranded 2x Cu 1.5...6 mm ²
Conventional Free-air Thermal Current (I _{th}):	16 A
Conventional Thermal Current (I _{the}):	16 A
Fourth Pole Position:	Right Side
Fourth Pole Type:	Switched - Simultaneous Function Switched - Late-break and Early-make
Handle Color:	Black
Handle Length:	28.5 mm
Handle Type:	Knob
Lock Type:	Padlockable
Maximum Mounted Auxiliary Contacts:	4 NO, 4 NC
Mechanical Durability:	Nr. Operations 100000
Mounting Type:	Base/DIN mounting
Number of Poles:	4P
Operating Mode:	Front
Position of Line Terminals:	Top In - Bottom Out Bottom In - Top Out
Power Loss:	at Rated Operating Conditions per Pole 0.1 W
Rated Impulse Withstand Voltage (U _{imp}):	8 kV
Rated Insulation Voltage (U _i):	acc. to IEC 60947-1 800 V
Rated Operational Current AC-21A (I _e):	(415 V) 16 A (500 V) 16 A (690 V) 16 A
Rated Operational Current AC-22A (I _e):	(415 V) 16 A (500 V) 16 A (690 V) 16 A
Rated Operational Current AC-23A (I _e):	(415 V) 16 A (500 V) 16 A (690 V) 16 A

Rated Operational Power AC-23A (P_e):	(415 V) 7.5 kW (500 V) 9 kW (690 V) 11 kW
Rated Operational Voltage:	Main Circuit 800 V
Rated Short-Circuit Making Capacity (I_{cm}):	(690 V) 1.76 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 0.8 kA for 0.2 s 1.25 kA
Recommended Screw Driver:	Main Circuit Pozidriv 2
Switches Operating Mechanism:	Mechanism on Top of the Switch
Terminal Type:	Screw Terminals
Tightening Torque:	acc. IEC 60947-1 1 N·m
Wire Stripping Length:	Main Circuit 9-10 mm Main Circuit 0.35-0.39 in

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	600 V
Ampere Rating:	20 A
Horsepower Rating UL/CSA:	(110 ... 120 V AC) Single Phase 1 Hp (240 V AC) Single Phase 2 Hp (440 ... 480 V AC) Single Phase 5 Hp (550 ... 600 V AC) Single Phase 7.5 Hp (240 V AC) Three Phase 5 Hp (440 ... 480 V AC) Three Phase 10 Hp (550 ... 600 V AC) Three Phase 10 Hp
Wire Size:	1x 18-6 AWG 2x 16-10 AWG
Tightening Torque UL/CSA:	UL 1 lbf·in

Certificates and Declarations

CCC Certificate:	CCC OT16-63G1
Declaration of Conformity - CE:	1SCC301348D2701
DNV Certificate:	1SCC301347D0201
UL Certificate:	1SCC301345D0201

External Classifications and Standards

ETIM 9:	EC000216 - Switch disconnecter (low voltage)
ETIM 10:	EC000216 - Switch disconnecter (AC)
UNSPSC:	39122233
IDEA Granular Category Code (IGCC):	5290 >> Disconnect switch
eClass:	V11.1 : 27371403
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland):	3660579
E-Number (Sweden):	3172216

Categories

Products > Low Voltage Products and Systems > Switches > Switch Disconnectors




ABB
Eco
Solutions™