



PRODUCT-DETAILS

OZXT2x50

OZXT2X50 TERMINAL SET Al/Cu 2x(16...50mm2) (3 PCS)



General Information	
Extended Product Type:	OZXT2x50
Product ID:	1SCA163565R1001
EAN:	6417019931623
Catalog Description:	OZXT2X50 TERMINAL SET Al/Cu 2x(16...50mm2) (3 PCS)
Long Description:	Terminal clamps for Al/Cu 2x(16...50mm2) cables. Packaging includes 3 pcs. Suitable for OT Plus switch disconnectors OT30G3-...OT160G3-
Display Name:	OZXT2x50

Material Compliance	
Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	1SCC011021D0201
RoHS Declaration:	1SCC011020D0201
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA:	1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information:	9AKK108468A5537 1SCC301020C0201
------------------------------------	------------------------------------

Instructions and Manuals:	1SCC390197M0201
---------------------------	-----------------

Mechanical Drawings:	OZXT2X50.STP
----------------------	--------------

Ordering

Minimum Order Quantity:	1 piece
-------------------------	---------

Customs Tariff Number:	85389099
------------------------	----------

Country of Origin:	Finland
--------------------	---------

Dimensions

Product Net Width:	22.4 mm
--------------------	---------

Product Net Height:	41.2 mm
---------------------	---------

Product Net Depth / Length:	71.8 mm
-----------------------------	---------

Product Net Weight:	0.057 kg
---------------------	----------

Container Information

Package Level 1 Units:	bag 3 piece
------------------------	-------------

Package Level 1 Width:	150 mm
------------------------	--------

Package Level 1 Depth / Length:	100 mm
---------------------------------	--------

Package Level 1 Height:	40 mm
-------------------------	-------

Package Level 1 Gross Weight:	0.175 kg
-------------------------------	----------

Package Level 1 EAN:	6417019931623
----------------------	---------------

Technical

Cable Cross-Section:	Cu 6...50 mm ² Al 16...50 mm ²
----------------------	---

Conventional Thermal Current (I _{the}):	320 A
---	-------

Rated Insulation Voltage (U _i):	acc. to IEC 60947-1 690 V
---	---------------------------

Rated Operational Voltage:	Main Circuit 690 V
----------------------------	--------------------

Recommended Screw Driver:	Main Circuit Hexagon
---------------------------	----------------------

Terminal Type:	Screw Terminals
----------------	-----------------

Tightening Torque:	acc. IEC 60947-1 6...10 N·m
--------------------	-----------------------------

Wire Stripping Length:	Main Circuit 18.5 mm
	Main Circuit 32.0 mm
	Main Circuit 1.10 in
	Main Circuit 1.26 in

External Classifications and Standards

ETIM 9:	EC002498 - Accessories/spare parts for low-voltage switch technology
ETIM 10:	EC002498 - Accessories/spare parts for low-voltage switch technology
UNSPSC:	39122221
IDEA Granular Category Code (IGCC):	5219 >> Switch part or accessory
eClass:	V11.1 : 27371392
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland):	3660478
E-Number (Sweden):	2670890

Categories

Products > Low Voltage Products and Systems > Switches > Switch Disconnectors

