


PMF

FLAT HOLDERS, FOR FLAT TAGS, PLASTICIZED PVC



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40°C
Maximum operating temperature	80°C
Colour	transparent

CLASSIFICATION AND DATA ORDERING

Customs code	39269097
--------------	----------

CERTIFICATIONS

Self-extinguishing fire class according to UL 94	V0
--	----



PMF-00

Range of cable cross section [mm²]

0.25

Ø [mm]

1.3

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
90000	Plasticised PVC	4.8	10	8000	8000	Yes	Yes
90020	Plasticised PVC	4.8	15	6000	6000	Yes	Yes
90040	Plasticised PVC	4.8	20	4000	4000	Yes	Yes
90090	Plasticised PVC	4.8	40	1500	1500	Yes	Yes
90070	Plasticised PVC	4.8	15	2000	2000	Yes	Yes
90010	Plasticised PVC	4.8	12	7000	7000	Yes	Yes

PMF-01

Range of cable cross section [mm²]

0.5

Ø [mm]

2

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
90100	Plasticised PVC	5	10	6000	6000	Yes	Yes
90110	Plasticised PVC	5	12	5000	5000	Yes	Yes
90120	Plasticised PVC	5	15	4000	4000	Yes	Yes
90140	Plasticised PVC	5	20	3000	3000	Yes	Yes
90170N	Plasticised PVC	5	30	1500	1500		Yes
90180	Plasticised PVC	5	1000	25	25	Yes	Yes
90190N	Plasticised PVC	5	40	500	500		Yes

PMF-02

Range of cable cross section [mm²]

2.5

Ø [mm]

3.4

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
90200	Plasticised PVC	5.1	10	4000	4000	Yes	Yes
90210	Plasticised PVC	5.1	12	3000	3000	Yes	Yes
90220	Plasticised PVC	5.1	15	2500	2500	Yes	Yes
90240	Plasticised PVC	5.1	20	2000	2000	Yes	Yes
90270N	Plasticised PVC	5.1	30	500	500		Yes
90290N	Plasticised PVC	5.1	40	500	500		Yes

PMF-03

Range of cable cross section [mm²]

4

Ø [mm]

4

tipo	Material	Silicone-free	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
90300	Plasticised PVC		7.6	10	3000	3000	Yes	Yes
90310	Plasticised PVC		7.6	12	2000	2000	Yes	Yes
90320	Plasticised PVC		7.6	15	1500	1500	Yes	Yes

tipo	Material	Silicone-free	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
90370N	Plasticised PVC		7.6	30	500	500		Yes
90340	Plasticised PVC		7.6	20	1000	1000	Yes	Yes
90390		Yes	4	40	1000	1000	Yes	
90390N	Plasticised PVC		7.6	40	500	500		Yes

PMF-04

Range of cable cross section [mm²]

10

Ø [mm]

6

tipo	Material	Silicone-free	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
90400	Plasticised PVC		9	10	2000	2000	Yes	Yes
90410	Plasticised PVC		9	12	1000	1000	Yes	Yes
90420	Plasticised PVC		9	15	1000	1000	Yes	Yes
90440N	Plasticised PVC		9	20	1000	1000		Yes
90470	Plasticised PVC		9	30	500	500	Yes	Yes
90490		Yes	4	40	500	500	Yes	
90490N	Plasticised PVC		9	40	250	250		Yes

PMF-05

Range of cable cross section [mm²]

25

Ø [mm]

9

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
90500	Plasticised PVC	15.9	10	500	500	Yes	Yes
90510	Plasticised PVC	15.9	12	500	500	Yes	Yes
90520N	Plasticised PVC	15.9	15	500	500		Yes
90540	Plasticised PVC	15.9	20	250	250	Yes	Yes
90570N	Plasticised PVC	15.9	30	250	250		Yes
90590	Plasticised PVC	15.9	40	100	100	Yes	Yes

PMF-06

Range of cable cross section [mm²]

70

Ø [mm]

14

tipo	Material	Width [mm]	L [mm]	Unit in minimal packaging [pce]	Unit in standard packaging [pce]	ROHS compliant	EN ISO 4892-2
90600	Plasticised PVC	20.4	10	500	500	Yes	Yes
90610	Plasticised PVC	20.4	12	250	250	Yes	Yes
90620	Plasticised PVC	20.4	15	250	250	Yes	Yes
90640N	Plasticised PVC	20.4	20	200	200		Yes
90670	Plasticised PVC	20.4	30	100	100	Yes	Yes
90690	Plasticised PVC	20.4	40	100	100	Yes	Yes

