

Product datasheet

Specifications



Molded case circuit breaker,
PowerPacT 4, 3P, Icu 36kA, TMD
thermal magnetic trip unit, 32A
rating

PP40323X

EAN Code: 5018934030104

Main

Range of product	PowerPacT 4
Product or component type	Circuit breaker
Device application	Distribution
Poles description	3P
[In] rated current	32 A at 40 °C
[Ue] rated operational voltage	415 V AC 50/60 Hz
Suitability for isolation	Yes conforming to BS EN 60947-2
Utilisation category	Category A
[Icu] rated ultimate short-circuit breaking capacity	36 kA Icu at 415 V AC 50/60 Hz
Performance level	F
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
Control type	Toggle
Circuit breaker mounting mode	Panel-mounted

Complementary

[Ui] rated insulation voltage	800 V
[Uimp] rated impulse withstand voltage	8 kV
[Ics] rated service short-circuit breaking capacity	36 kA at 415 V AC 50/60 Hz
Mechanical durability	50000 cycles
Electrical durability	50000 cycles at 440 V In/2 30000 cycles at 440 V In
Power dissipation per pole	4.03 W
Mounting support	Backplate
Mounting position	Horizontal and vertical
Number of modules	3 module(s)35 mm
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rating	32 A at 40 °C
Long-time pick-up adjustment type Ir (thermal protection)	Fixed

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

[Ir] long-time protection pick-up adjustment range	0.7...1 x In
Long-time protection delay adjustment type tr	Fixed
Instantaneous protection pick-up adjustment type li	Fixed
[Ii] instantaneous protection pick-up adjustment range	400 A
Earth-leakage protection	Without
Contact position indicator	Yes
Width	105 mm
Depth	86 mm
Height	161 mm
Product weight	2.05 kg
Product destination	250 A panelboard 400/630 A panelboard
Colour	Grey

Environment

Standards	BS EN 60947-2
Electrical shock protection class	Class II
Pollution degree	3 conforming to EN/IEC 60664-1
IP degree of protection	IP40 conforming to EN/IEC 60529
IK degree of protection	IK07 conforming to EN/IEC 62262
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C
Operating altitude	0...2000 m without derating 2000...5000 m with derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.000 cm
Package 1 Width	25.500 cm
Package 1 Length	25.500 cm
Package 1 Weight	3.347 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	84
Package 2 Height	100.000 cm
Package 2 Width	100.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	340.880 kg

Logistical informations

Country of origin	GB
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	26071879-056e-4394-a5a3-489ecef1b26f
EU RoHS Directive	Compliant By Exemption
Halogen-free status	Product contains halogen above thresholds

Use Longer

Lifetime extension	
Repair	No

Use Again

Repack and remanufacture	
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative



