

RT-TAPW

9mm PROFILES, RIGID PVC



Features

TECHNICAL INFORMATION

Maximum operating temperature	90°C
Minimum application temperature	10°C
Maximum application temperature	40°C

WEIGHT AND DIMENSIONS

Width	9mm
-------	-----

CLASSIFICATION AND DATA ORDERING

Customs code	39269097
--------------	----------

MATERIAL COMPOSITION AND TREATMENTS

Material	Dielectric rigid PVC
----------	----------------------

LOGISTIC

Unit in minimal packaging	25PCE
Unit in standard packaging	25PCE

CERTIFICATIONS

ROHS compliant	Yes
Self-extinguishing fire class according to UL 94	V0



RTA-TAPW

tipo	Colour	Type of adhesive	L [mm]
990655N	black	spongy acrylic-based adhesive	430
990795N	black	spongy acrylic-based adhesive	650
990527N	black	spongy acrylic-based adhesive	1000
990653N	grey	spongy acrylic-based adhesive	430
990793N	grey	spongy acrylic-based adhesive	650
990506N	grey	spongy acrylic-based adhesive	1000

RTR-TAPW

tipo	Colour	L [mm]
990505	grey	1000
990652	grey	430
990792	grey	650
990526	black	1000
990654	black	430
990794	black	650