

Product datasheet

Specifications



standard Network Interface Module STB - CANopen bus - 1 Mbit/s

Local distributor code:

389839248

STBNCO2212

⚠ To be discontinued on: 1 Dec 2027

⚠ To be end-of-service on: 31 Dec 2035

⚠ To be discontinued

EAN Code: 3595862055154

Main

Range of product	Modicon STB distributed I/O solution
Product or component type	Standard Network Interface Module

Complementary

Integrated connection type	CANopen bus conforming to CIA DS-301 9-way male SUB-D connector double shielded twisted pair (bus) CANopen bus conforming to CIA DS-301 HE-13 (RS232 port) CANopen bus conforming to CIA DS-301 8-way female (RS232 port)
Number of segments	1 primary, maximum 6 extensions
Number of server device(s)	127
Structure type	CAN field bus
Number of addressable I/O module	0...32 per island
Input current	430 mA for supply circuit
Nominal output current	0.575 A at 60...70 °C 1.2 A
Output voltage	5.25 V DC (tolerance: +/- 0.21 %) for logic bus
Electromagnetic compatibility	Immunity to electromagnetic interference conforming to IEC 61131-2
Transmission rate	1 Mbit/s
Communication service	Service Data Object (SDO) Network management (NMT) Process Data Object (PDO)
Power supply type	SELV
Local signalling	1 LED green for CAN RUN 1 LED green for island state (RUN) 1 LED green for power supply (PWR) 1 LED red for CAN ERR 1 LED red for module error (ERR) 1 LED yellow for test mode
Height	40 mm
Width	128.3 mm
Depth	70 mm
Product weight	0.135 kg

Environment

IP degree of protection	IP20
Marking	CE

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	ATEX Cat 3G FM Class 1 Division 2 CSA UL C-Tick
Ambient air temperature for operation	0...60 °C without derating -25...70 °C with derating factor
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % at 60 °C without condensation
Operating altitude	<= 2000 m
Vibration resistance	3 gn (f = 58...150 Hz) on 35 mm DIN rail 5 gn (f = 58...150 Hz) on 35 mm DIN rail +/-0.35 mm (f = 10...58 Hz)
Shock resistance	30 gn for 11 ms conforming to IEC 88 reference 2-27

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.300 cm
Package 1 Width	7.200 cm
Package 1 Length	13.000 cm
Package 1 Weight	169.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	5.640 kg

Logistical informations

Country of origin	FR
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

No

Packaging without single use plastic

No

SCIP Number

F760fd97-89c1-4651-a374-9b8eff254b6a

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

No

Dimensions Drawings

Dimensions

