



Features & Benefits

- Supplied with mounting bracket
- Wind speed accuracy $\pm 2\%$
- Anodized aluminium housing
- Ideal for naturally ventilated building applications
- Easy installation

Technical Overview

The AV-W series measures the wind speed and direction, providing output signals compatible with most BEMS controllers. Intended for applications where external weather conditions influence the building control strategy, such as for the automatic closing of windows in high wind conditions. Mounting kit is included.

Specification

Accuracy	$\pm 2\%$
Ambient Range	-20 to +70°C
Contact rating Current	1A max.
Contact rating Power	50W max. (dc resistive)
Contact Rating Voltage	100Vdc max
Country of origin	UK
Dimensions	Height 280mm (max. arc 120mm)
Electrical connections	Flying lead (3m long)
Electrical Travel	357° ($\pm 2^\circ$)
Gross Weight (kg)	1.45
Mechanical travel	360° endless travel
Min. start speed	0.5m/s (98ft/min) typically
Output	1 contact closure per 1.493 metre (zero bounce)
Protection	IP65
Weight	1.45kg

Technical Specification

Ambient Range	-20 to +70°C
Weight	1.45kg
Output	1 contact closure per 1.493 metre (zero bounce)

Tel: +44 (0)1732 861200 | E-mail: sales@sontay.com | Web: www.sontay.com

Sontay Limited. Four Elms Road, Edenbridge, Kent, TN8 6AB UK

Dimensions	Height 280mm (max. arc 120mm)
Country of origin	UK

Related Product Codes

AV-W-AD	Wind Speed and Direction Transmitter
AV-W-S	Wind Speed Transmitter