



### Features & Benefits

- Auto-detection 0-10Vdc or 4-20mA output, 3-wire only
- Fully configurable LCD Display
- Resistive temperature output option
- Set point and Momentary switch options
- No jumpers or DIP-switches to select output type

### Technical Overview

The GS-AQ-x-UN range offers a cost-effective single output for air quality measurement. These can also include a combination of familiar passive options such as temperature, set point adjustment & momentary switch plus an LCD display. A unique feature of the sensor is its ability to automatically detect what sort of controller input it is connected to, 4-20mA or 0-10Vdc, removing the requirement for output jumpers which can be inadvertently set incorrectly. Just connect it to the controller input and it does the rest. PCB LED indication of which output type is in operation is provided, with diagnostic LED patterns for determining faults.

### Specification

|                                   |                                           |
|-----------------------------------|-------------------------------------------|
| Active outputs                    | 0-10Vdc or 4-20mA (3-wire) self-detecting |
| Environmental Housing             | 0 to 50°C, 0 to 95% RH non-condensing     |
| Gross Weight (kg)                 | 0.20                                      |
| Housing dimensions                | 115 x 85 x 30mm                           |
| Housing material                  | ABS (flame retardant)                     |
| Optional passive output           | PTC/NTC Element Any Sontay resistive type |
| Output range                      | 0 to 100% (0=good / 100=poor)             |
| Override optional passive outputs | VFC                                       |
| Power supply                      | 24Vac/dc $\pm 10\%$                       |
| Protection                        | IP30                                      |
| Setpoint optional passive outputs | 1-11k $\Omega$                            |
| Weight                            | 200g                                      |

### Technical Specification

|                         |                                           |
|-------------------------|-------------------------------------------|
| Optional passive output | PTC/NTC Element Any Sontay resistive type |
| Housing dimensions      | 115 x 85 x 30mm                           |
| Weight                  | 200g                                      |
| Housing material        | ABS (flame retardant)                     |

Tel: +44 (0)1732 861200 | E-mail: [sales@sontay.com](mailto:sales@sontay.com) | Web: [www.sontay.com](http://www.sontay.com)

Sontay Limited. Four Elms Road, Edenbridge, Kent, TN8 6AB UK

|                       |                                           |
|-----------------------|-------------------------------------------|
| <b>Active outputs</b> | 0-10Vdc or 4-20mA (3-wire) self-detecting |
| <b>Output range</b>   | 0 to 100% (0=good / 100=poor)             |
| <b>Power supply</b>   | 24Vac/dc $\pm 10\%$                       |

### Related Product Codes

|                   |                                              |
|-------------------|----------------------------------------------|
| <b>GS-AQ-S-UN</b> | Space Air Quality Trans. Single Analogue Out |
| <b>-BLK</b>       | Space Air Quality Trans. Single Analogue Out |
| <b>-LCD</b>       | Space Mounted Air Quality Sensor with LCD    |
| <b>-MS</b>        | Space Air Quality Trans. Single Analogue Out |
| <b>-SP</b>        | Space Air Quality Trans. Single Analogue Out |
| <b>-T</b>         | Space Air Quality Trans. Single Analogue Out |