



Features & Benefits

- Robust housing
- Immersion sensors supplied with pocket
- Ideal for many applications
- Volt free contacts
- Concealed adjustment

Technical Overview

Sontay's range of thermostats are well suited for a number of applications of temperature control or safety cut-out in pipe work systems, calorifiers, duct work systems, green houses and many other installations. They all have the set-point adjustment under the cover to prevent unauthorised tampering.

Specification

Ambient relative humidity	0 to 95% non-condensing
Ambient Temperature Range	-35 to +65°C
Capillary length (ST-C)	1.5m
Control range	50 to 140°C
Dimensions	108 x 70 x 72mm
Gross Weight (kg)	0.36
Housing Material	ABS (flame resistant)
Protection	IP43
Sensing element	Liquid filled copper element
Switch rating	24 to 250Vac @ 16(4)A
Weight	340g

Technical Specification

Ambient Temperature Range	-35 to +65°C
Weight	340g
Dimensions	108 x 70 x 72mm
Housing Material	ABS (flame resistant)

Related Product Codes

ST-C-01M	Capillary Thermostat 50-140°C Manual Reset
ST-D-01A	Duct Thermostat -35 To +35deg C Auto Reset
ST-D-02A	Duct Thermostat 0 to 90 degC Auto Reset
ST-D-03A	Duct Thermostat -30 To +30°C Auto Reset
ST-D-04M	Duct Thermostat 0 To +90°C Manual Reset
ST-I-01A	Immersion Thermostat 0 to 120C Auto Reset
ST-I-02M	Immersion Thermostat 0 to 110C Manual Reset
ST-I-03M	Immersion Thermostat 20 to 90C Manual Reset
ST-IMM-PKT	Immersion Pocket Stainless Steel Replacement
ST-S-02A	Strap-On Thermostat 0-90C Auto Reset
ST-W-01A	Wall Thermostat -30 To +30 degC Auto Reset