

Features & Benefits

- Designed to be aesthetically pleasing
- Blends into the fabric of any building
- Meets exacting standards of today's specifiers
- LCD display options on -ACT models

Technical Overview

This range of innovative space sensors is designed to meet the exacting standards of today's architects, specifiers and building owners. Its unique low profile, curved style allows it to blend seamlessly into the architecture of modern and older buildings alike. As with its predecessor the TT-S range can be supplied with a wide range of user interface options such as set-point adjustment, fan speed and momentary switches etc. to give the customer additional functionality. Sontay also offers a complete range of customised user interfaces for every requirement.

Specification

Dimensions	115 x 85 x 30mm
Environmental Housing	-10 to 60°C 0 to 95% non-condensing
Gross Weight (kg)	0.15
Housing Material	ABS (flame retardant)
Output range	0 to 40°C
Power Supply	24Vac/dc ±10%
Protection	IP30
Weight	120g

Technical Specification

Weight	120g
Dimensions	115 x 85 x 30mm
Housing Material	ABS (flame retardant)
Output range	0 to 40°C
Power Supply	24Vac/dc ±10%

Related Product Codes

TT-S-ACT

-LCD	Space Mounted Active Temperature Sensor LCD
-SP	Space Mounted Active Temperature Sensor SP