

Specifications



2203504

ZA2BD2

EAN Code: 3389110645309

Range of product	Harmony XAC
Product or component type	Selector switch
Component name	ZA2
Product compatibility	XACA

Product weight	0.018 kg
Cap/operator or lens colour	Black
Marking	Unmarked
Mounting location	Base of enclosure Front of enclosure
Sale per indivisible quantity	1

Standards	CSA C22.2 No 14 IEC 60947-5-1 IEC 60204-32 UL 508
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Vibration resistance	15 gn (f= 10...500 Hz) conforming to IEC 60068-2-6
Shock resistance	100 gn conforming to IEC 60068-2-27
Overvoltage category	Class II conforming to IEC 61140
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	4.0 cm
Package 1 Length	5.0 cm
Package 1 Weight	21.0 g
Unit Type of Package 2	BB1

Number of Units in Package 2	10
Package 2 Height	5.0 cm
Package 2 Width	20.0 cm
Package 2 Length	20.0 cm
Package 2 Weight	215.0 g
Unit Type of Package 3	S02
Number of Units in Package 3	100
Package 3 Height	15.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	2.477 kg

Logistical informations

Country of origin	FR
-------------------	----

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	0.1 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.1 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	84
End of life manual availability	End of Life Information
Take-back	No

Offer Marketing Illustration

Product benefits / Features

Pendant Control Stations

Harmony XAC



Configure your product to match your needs



A complete solution for industrial machine control



Easy to adapt and maintain



Ready to use, even in harsh environments



Offer Marketing Illustration

Product benefits / Features

Technical Features

Harmony XAC

Compliance with IEC standards, CE marking and CSA certification

Operating temperature:
-25°C to + 70°C

Resistance to harsh conditions:

- IP65 protection degree
- Shocks resistance IK08

Double insulation: protection from electrical hazards

Up to 12 buttons + E-Stop, with up to 3 movements

Empty enclosure or complete ready for use